

Printing date: 21.12.2022 Version number 4 (replaces version 3) Revision: 21.12.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Additive WS+ for WhiteStar® DIP+
Zusatz WS+ für WhiteStar® DIP+

· Article number: 81016110

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Not approved for private consumers.
- · Application of the substance / the mixture Galvanic bath
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Heimerle + Meule GmbH Dennigstrasse 16 D-75179 Pforzheim

Telefon +49 (0) 7231 940-0 Telefax +49 (0) 7231 940-2199 www.heimerle-meule.com

· Further information obtainable from:

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt Department BASU - Construction / Occupational Safety / Environment sds@heimerle-meule.com

IATA - 24h Emergency Contact - IATA - 24h Emergency Contact - (Dangerous goods emergency number) +49 172 739 6970

· 1.4 Emergency telephone number:

DEUTSCHLAND - GERMANY:

Vergiftungs-Informations-Zentrale Freiburg, ++49 761 19240 (24 h)

(Poisoning Information Center)

GREAT BRITAIN:

National Poisons Information Service +44 121 507 4123

Members of the public seeking specific information on poisons should contact: In England and Wales: NHS 111 - dial 111 - In Scotland: NHS 24 - dial 111

In England and wates. MID III - dial III

IRELAND

+353 1 809 2166 (7 Days 8 am -10 pm) Healthcare Professionals: +353 1 809 2566

ITALY:

*Istituto Superiore di Sanità (ISS) +3906499906140* 

Centro Antiveleni

Bergamo: +39 800 883300 Firenze +39 055 794 7819 Milano: +39 055 794 7819 Roma +39 06 68593726

Roma +39 06 49978000

Roma +39 06 3954343

KROATIA - REPUBLIKA HRVATSKA:

(+385) 01 2348 342

ESTLAND - ESTONIA:

Tervisemeti Mürgistusteabekeskuse

National (24/7): 16662 (+372) 7943 794

LETTLAND - LATVIA:

Valsts Toksikoloģijas centrs, Saindēšanās un zāļu informācijas centrs,

(Contd. on page 2)



Printing date: 21.12.2022 Version number 4 (replaces version 3) Revision: 21.12.2022

Trade name: Additive WS+ for WhiteStar® DIP+ Zusatz WS+ für WhiteStar® DIP+

(Contd. of page 1)

(24h) 112

(24h) +371 67042473

LITAUEN - LIETUVOS RESPUBLIKA:

Poison Information Bureau (24/7), Tel.: +8 5 236 20 52

Apsinuodijimų informacijos biuras

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

*P264* Wash thoroughly after handling.

*P280* Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P337+P313 If eye irritation persists: Get medical advice/attention.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



Printing date: 21.12.2022 Version number 4 (replaces version 3) Revision: 21.12.2022

Trade name: Additive WS+ for WhiteStar® DIP+ Zusatz WS+ für WhiteStar® DIP+

(Contd. of page 2) Dangerous components / Information on ingredients: CAS: 636-73-7 pyridine-3-sulphonic acid <5% EINECS: 211-265-9 🕩 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 CAS: 7664-93-9 sulphuric acid; sulfuric acid <8% EINECS: 231-639-5 Met. Corr.1, H290; Skin Corr. 1A, H314 Specific concentration limits: Skin Corr. 1A; H314: C ≥ 15 % Index number: 016-020-00-8 Reg.nr.: 01-2119453338-20 Skin Irrit. 2; H315:  $5\% \le C < 15\%$ 

Eye Irrit. 2; H319:  $5\% \le C < 15\%$ 

## SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

Involve doctor immediately after a accident or unwell

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment:



Wear self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

(Contd. on page 4)

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.



Printing date: 21.12.2022 Version number 4 (replaces version 3) Revision: 21.12.2022

Trade name: Additive WS+ for WhiteStar® DIP+
Zusatz WS+ für WhiteStar® DIP+

(Contd. of page 3)

Only handle and refill product in closed systems.

### · 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

### · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

### · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

### · 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

he usual precautionary measures are to be adhered to when handling chemicals.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not dry clean dust covered objects and floors. Wash thoroughly with plenty of water.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Observe official regulations on storing packagings.

Observe official regulations on storing packagings .

Prevent any seepage into the ground.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 8 B
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

## · 8.1 Control parameters

	· Ingredients with limit values that require monitoring at the workplace:		
CAS: 7664-93-9 sulphuric acid		e acid	
	WEL (Great Britain)	Long-term value: 0.05* mg/m³ *mist: defined as thoracic fraction	
	IOELV (European Union)	Long-term value: 0.05 mg/m³	
		Long-term value: 0.1 E mg/m³ 1(I);DFG, EU, Y	

### Regulatory information

WEL (Great Britain): EH40/2020

IOELV (European Union): (EU) 2019/1831

AGW (Germany): TRGS 900

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.

(Contd. on page 5)

Heimerle + Meule
Heimerle + Meule

Printing date: 21.12.2022 Version number 4 (replaces version 3) Revision: 21.12.2022

Trade name: Additive WS+ for WhiteStar® DIP+ Zusatz WS+ für WhiteStar® DIP+

(Contd. of page 4)

#### · Individual protection measures, such as personal protective equipment

## General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

According to EC Directive 89/686/EEC

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire.

according EN 14387 according to EN 143

- · Recommended filter device for short term use: Combination filter B-P2
- · Hand protection



Protective gloves

#### according to EN 374

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

Sensibilisation by the components in the glove materials is possible.

Check the permeability prior to each anewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Prior to working with gloves the rubbing in with tanniferous skin-protecting agents for the avoidance of skin softening due to perspiration is recommended.

#### · Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.65$  mm

Chloroprene rubber, CR

Recommended thickness of the material:  $\geq 0.65$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

#### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 3).

*Value for the permeation: Level*  $\leq 3$ 

· Not suitable are gloves made of the following materials: Leather gloves

(Contd. on page 6)



Version number 4 (replaces version 3) Revision: 21.12.2022 Printing date: 21.12.2022

Trade name: Additive WS+ for WhiteStar® DIP+ Zusatz WS+ für WhiteStar® DIP+

(Contd. of page 5)

· Eye/face protection



Tightly sealed goggles

according to EN 166

· Body protection: Protective work clothing

## SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid · Colour: Colourless · Odour: **Odourless** · Odour threshold: Not determined. Undetermined. · Melting point/freezing point:

· Boiling point or initial boiling point and boiling

Undetermined. range · Flammability *Not applicable.* 

· Lower and upper explosion limit

Not determined. · Lower: · Upper: Not determined. · Flash point: *Not applicable.* · Decomposition temperature: Not determined. 2.5

· pH at 20°C (68°F)

· Viscosity:

Not determined. · Kinematic viscosity Not determined. · Dynamic:

Solubility

Fully miscible. · water: Not determined. · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure:

· Density and/or relative density

1.08 g/cm³ (9.01 lbs/gal) Density at 20°C (68°F):

Not determined. · Relative density Not determined. · Vapour density

9.2 Other information

· Appearance:

· Form: Liquid

· Important information on protection of health and

environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

· Solvent content:

0.0% · Organic solvents:

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Void · Explosives Void · Flammable gases

(Contd. on page 7)



Printing date: 21.12.2022 Version number 4 (replaces version 3) Revision: 21.12.2022

Trade name: Additive WS+ for WhiteStar® DIP+ Zusatz WS+ für WhiteStar® DIP+

		(Contd. of page
· Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
· Flammable liquids	Void	
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Reaktions with metalls
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment Not applicable.
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 8)



Printing date: 21.12.2022 Version number 4 (replaces version 3) Revision: 21.12.2022

Trade name: Additive WS+ for WhiteStar® DIP+ Zusatz WS+ für WhiteStar® DIP+

(Contd. of page 7)


- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

At present there are no ecotoxicological assessments.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

· Waste disposal key:

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Packaging which is uncleaned or soiled with product remains is to be treated like the product itself Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

OF OWLOW!	4 70		
	A. Tranchar	tintorm	ation
<b>SECTION</b> 1	T. II WIISPUI	i ilijoi m	uuvuu

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3264
· 14.2 UN proper shipping name · ADR · IMDG, IATA	UN3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (SULPHURIC ACID) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (SULPHURIC ACID)

- · 14.3 Transport hazard class(es)
- · ADR, IMDG, IATA



· Class	8 Corrosive substances.
· Lahel	8

· 14.4 Packing group

· ADR, IMDG, IATA

(Contd. on page 9)



Printing date: 21.12.2022 Version number 4 (replaces version 3) Revision: 21.12.2022

Trade name: Additive WS+ for WhiteStar® DIP+ Zusatz WS+ für WhiteStar® DIP+

	(Contd. of page
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Corrosive substances.
Hazard identification number (Kemler code):	80
EMS Number:	F- $A$ , $S$ - $B$
Segregation groups	(SGG1) Acids
Stowage Category	A
Stowage Code	SW2 Clear of living quarters.
14.7 Maritime transport in bulk according to IM	10
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IATA	
Remarks:	
	24h emergency contact -
	(Dangerous goods emergency number)
	+49 172 739 6970
UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIO
	N.O.S. (SULPHURIC ACID), 8, III

## **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

#### · GADSL - Global Automotive Declarable Substance List

None of the ingredients is listed.

- · National regulations:
- · Waterhazard class: .
- · Other regulations, limitations and prohibitive regulations -

(Contd. on page 10)



Printing date: 21.12.2022 Version number 4 (replaces version 3) Revision: 21.12.2022

Trade name: Additive WS+ for WhiteStar® DIP+ Zusatz WS+ für WhiteStar® DIP+

(Contd. of page 9)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Reasons for revise

If necessary, this saftey data sheet can revised according to legal guidelines.

Our current version for your reference is available on our website www.heimerle-meule.com

### · Relevant phrases

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

#### Department issuing SDS:

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt Department BASU - Construction / Occupational Safety / Environment

sds@heimerle-meule.com

### · Contact:

Herr Thomas Knuth

thomas.knuth@heimerle-meule.com

sds@heimerle-meule.com

### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

AwSV: Ordinance on facilities for handling water-polluting substances (German regulation).

TRGS: Technical rules for hazardous substances (German regulation)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Met. Corr.1: Corrosive to metals - Category 1

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.

GB ·