

Printing date: 14.12.2022 Version number 9 (replaces version 8) Revision: 14.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name: Brightener A for SCANDIA 360 Glanzzusatz A für SCANDIA 360

· Article number: 86938810

· 1.2 Relevant identified uses of the substance or mixture and uses advised against Not approved for private consumers.

· Application of the substance / the mixture

Electroplating auxiliary

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Heimerle + Meule GmbH Dennigstrasse 16 D-75179 Pforzheim

Telefon +49 (0) 7231 940-0 Telefax +49 (0) 7231 940-2199 www.heimerle-meule.com

Further information obtainable from:

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt Department BASU - Construction / Occupational Safety / Environment sds@heimerle-meule.com

IATA - 24h Emergency Contact - IATA - 24h Emergency Contact - (Dangerous goods emergency number) +49 172 739 6970

· 1.4 Emergency telephone number:

DEUTSCHLAND - GERMANY:

Vergiftungs-Informations-Zentrale Freiburg, ++49 761 19240 (24 h)

(Poisoning Information Center)

GREAT BRITAIN:

National Poisons Information Service +44 121 507 4123

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111 - In Scotland: NHS 24 - dial 111 IRELAND

+353 1 809 2166 (7 Days 8 am -10 pm)

Healthcare Professionals: +353 1 809 2566

ITALY:

Istituto Superiore di Sanità (ISS) +3906499906140

Centro Antiveleni

Bergamo: +39 800 883300 Firenze +39 055 794 7819 Milano: +39 055 794 7819 Roma +39 06 68593726

Roma +39 06 49978000 Roma +39 06 3954343

KROATIA - REPUBLIKA HRVATSKA:

 $\frac{(+385)\ 01\ 2348\ 342}{(+385)\ 01\ 2348\ 342}$

ESTLÁND - ESTONIA:

Tervisemeti Mürgistusteabekeskuse

National (24/7): 16662 (+372) 7943 794

(Contd. on page 2)



Printing date: 14.12.2022 Version number 9 (replaces version 8) Revision: 14.12.2022

Trade name: Brightener A for SCANDIA 360 Glanzzusatz A für SCANDIA 360

(Contd. of page 1)

LETTLAND - LATVIA:

Valsts Toksikoloģijas centrs, Saindēšanās un zāļu informācijas centrs,

(24h) 112

(24h) +371 67042473

LITAUEN - LIETUVOS RESPUBLIKA:

Poison Information Bureau (24/7), Tel.: +8 5 236 20 52

Apsinuodijimų informacijos biuras

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 3 H311 Toxic in contact with skin.

Acute Tox. 1 H330 Fatal if inhaled.



health hazard

STOT RE 2 H373 May cause damage to the thyroid through prolonged or repeated exposure.



Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS08

GHS05

GHS06

· Signal word Danger

Hazard-determining components of labelling:

Potassium cyanide potassium hydroxide

(Contd. on page 3)



Printing date: 14.12.2022 Version number 9 (replaces version 8) Revision: 14.12.2022

Trade name: Brightener A for SCANDIA 360 Glanzzusatz A für SCANDIA 360

(Contd. of page 2)

· Hazard statements

H301+H311 Toxic if swallowed or in contact with skin.

H330 Fatal if inhaled.

H314 Causes severe skin burns and eye damage.

H373 May cause damage to the thyroid through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P361+P364 Take off immediately all contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

EUH032 Contact with acids liberates very toxic gas.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components / Inform	· Dangerous components / Information on ingredients:		
CAS: 151-50-8	Potassium cyanide	1-<2.5%	
EINECS: 205-792-3 Index number: 006-007-00-5	Acute Tox. 1, H300; Acute Tox. 1, H310; Acute Tox. 1, H330		
Reg.nr.: 01-2119486407-29-xxxx	♦ STOT RE 1, H372		
	<i>№ Met. Corr.1, H290</i>		
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410 EUH032		
CAS: 1310-58-3	potassium hydroxide; caustic potash	1-<2%	
EINECS: 215-181-3 Index number: 019-002-00-8	Skin Corr. 1A, H314 Acute Tox. 4, H302		
RTECS: TT 2102000	Specific concentration limits: Skin Corr. 1A; H314: $C \ge 5$ %		
	Skin Corr. 1B; H314: 2 % ≤ C < 5 %		
	Skin Irrit. 2; H315: 0.5 % ≤ C < 2 %		
	<i>Eye Irrit.</i> 2; <i>H319</i> : 0.5 % ≤ <i>C</i> < 2 %		

· Additional information:

Contains a sulfide emulsifier (no hazardous substance).

For the wording of the listed hazard phrases refer to section 16.

. CD



Printing date: 14.12.2022 Version number 9 (replaces version 8) Revision: 14.12.2022

Trade name: Brightener A for SCANDIA 360 Glanzzusatz A für SCANDIA 360

(Contd. of page 3)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Involve doctor immediately.

Immediately remove any clothing soiled by the product.

Remove breathing equipment only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

Involve doctor immediately after a accident or unwell

· After inhalation:

Call a doctor immediately.

Take affected persons into fresh air and keep quiet.

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Call a doctor immediately.

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

A person vomiting while laying on their back should be turned onto their side.

Rinse out mouth and then drink plenty of water.

- · Information for doctor: Cyanides poisoning
- · 4.2 Most important symptoms and effects, both acute and delayed Cyanosis
- · Hazards Danger of gastric perforation.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Hydrogen cyanide (HCN)

Formation of very toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment:

Mount respiratory protective device.



Wear self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire

(Contd. on page 5)



Printing date: 14.12.2022 Version number 9 (replaces version 8) Revision: 14.12.2022

Trade name: Brightener A for SCANDIA 360 Glanzzusatz A für SCANDIA 360

(Contd. of page 4)

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Only handle and refill product in closed systems.

· 6.2 Environmental precautions:

Keep contaminated washing water and dispose of appropriately.

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

he usual precautionary measures are to be adhered to when handling chemicals.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not dry clean dust covered objects and floors. Wash thoroughly with plenty of water.

- Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings.

Observe official regulations on storing packagings.

Prevent any seepage into the ground.

· Information about storage in one common storage facility:

Do not store together with acids.

Store away from foodstuffs.

· Further information about storage conditions:

Keep container tightly sealed.

(Contd. on page 6)



Printing date: 14.12.2022 Version number 9 (replaces version 8) Revision: 14.12.2022

Trade name: Brightener A for SCANDIA 360 Glanzzusatz A für SCANDIA 360

(Contd. of page 5)



Store under lock and key and with access restricted to technical experts or their assistants only.

Store under lock and key and out of the reach of children.

- · Storage class: 6.1 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace: CAS: 151-50-8 Potassium cyanide		
WEL (Great Britain)	Short-term value: 5 mg/m³ Long-term value: 1 mg/m³	
IOELV (European Union)	Sk, as CN Short-term value: 5 mg/m³	
ACW (Community)	Long-term value: 1 mg/m³ Skin; as cyanide	
AGW (Germany)	Long-term value: 1 E mg/m³ 5(II);EU, H, Y	
CAS: 1310-58-3 potassium hydroxide		
WEL (Great Britain)	Short-term value: 2 mg/m³	

Regulatory information

WEL (Great Britain): EH40/2020

IOELV (European Union): (EU) 2019/1831

AGW (Germany): TRGS 900

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

According to EC Directive 89/686/EEC

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device only when aerosol or mist is formed.

Short term filter device:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire.

(Contd. on page 7)



Printing date: 14.12.2022 Version number 9 (replaces version 8) Revision: 14.12.2022

Trade name: Brightener A for SCANDIA 360 Glanzzusatz A für SCANDIA 360

(Contd. of page 6)

according EN 14387 according to EN 143

- · Recommended filter device for short term use: Filter B
- · Hand protection

Alkaline resistant gloves

Check protective gloves prior to each use for their proper condition.



according to EN 374

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

Sensibilisation by the components in the glove materials is possible.

Check the permeability prior to each anewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Prior to working with gloves the rubbing in with tanniferous skin-protecting agents for the avoidance of skin softening due to perspiration is recommended.

· Material of gloves

Chloroprene rubber, CR

Recommended thickness of the material: ≥ 0.65 mm

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.65 mm

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 3).

Value for the permeation: Level ≤ 3

· Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

· Eye/face protection



Tightly sealed goggles

according to EN 166

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- Physical state Fluid

(Contd. on page 8)



Printing date: 14.12.2022 Version number 9 (replaces version 8) Revision: 14.12.2022

Trade name: Brightener A for SCANDIA 360 Glanzzusatz A für SCANDIA 360

	(Contd. of page
Colour:	Dark brown
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	100°C (212°F)
Flammability	Not applicable.
Lower and upper explosion limit	11
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable.
Decomposition temperature:	Not determined.
pH at 20°C (68°F)	13
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	ivot determined.
water:	Fully miscible.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	ivoi determined.
Density and or relative density Density at 20°C (68°F):	1.03 g/cm³ (8.6 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined. Not determined.
•	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and	d
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classe	'S
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	void Void
* * *	void Void
Pyrophoric solids Salf haging substances and mixtures	v ota Void
Self-heating substances and mixtures	roiu
Substances and mixtures, which emit flammable	Void
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void

(Contd. on page 9)



Printing date: 14.12.2022 Version number 9 (replaces version 8) Revision: 14.12.2022

Trade name: Brightener A for SCANDIA 360

Glanzzusatz A für SCANDIA 360

(Contd. of page 8)

· Desensitised explosives

Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

Contact with acids releases very toxic gases

Reacts with acids, alkalis and oxidising agents.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Acids
- · 10.6 Hazardous decomposition products: Hydrogen cyanide (prussic acid)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

Toxic if swallowed or in contact with skin.

Fatal if inhaled.

· LD/LC50	· LD/LC50 values relevant for classification:		
ATE (Acua	ATE (Acute Toxicity Estimates)		
Oral		247 mg/kg	
Dermal	LD50	250 mg/kg	
Inhalative	LC50/4 h	0.25 mg/l	
0.40 1.11	G4G 151 50 0 D		

CAS	CAS: 151-50-8 Potassium cyanide			
Ora	l	LD50	5 mg/kg (Rat)	
Der	mal	LD50	5 mg/kg (ATE)	
Inho	alative	LC50/4 h	0.005 mg/l (ATE)	
CAS	CAS: 1310-58-3 potassium hydroxide			
Ora	ıl .	LD50	365 mg/kg (rat)	

- · Skin corrosion/irritation Causes severe skin burns and eye damage.
- · Serious eye damage/irritation Causes serious eye damage.
- · STOT-repeated exposure May cause damage to the thyroid through prolonged or repeated exposure.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment Not applicable.
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 10)

Heimerle + Meule
Heimerle + Meule

Printing date: 14.12.2022 Version number 9 (replaces version 8) Revision: 14.12.2022

Trade name: Brightener A for SCANDIA 360 Glanzzusatz A für SCANDIA 360

(Contd. of page 9)

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

-


Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

· Waste disposal key:

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Packaging which is uncleaned or soiled with product remains is to be treated like the product itself Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish

• Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN2922
· 14.2 UN proper shipping name · ADR	UN2922 CORROSIVE LIQUID, TOXIC, N.O.S. (POTASSIUM HYDROXIDE, POTASSIUM CYANIDE)
· IMDG, IATA	CORROSIVE LIQUID, TOXIC, N.O.S. (POTASSIUM HYDROXIDE, POTASSIUM CYANIDE)

- · 14.3 Transport hazard class(es)
- $\cdot ADR$



· Class 8 Corrosive substances.

(Contd. on page 11)



Printing date: 14.12.2022 Version number 9 (replaces version 8) Revision: 14.12.2022

Trade name: Brightener A for SCANDIA 360 Glanzzusatz A für SCANDIA 360

	(Contd. of page 10)
· Label	8+6.1
· IMDG	
8 6	
· Class · Label	8 Corrosive substances. 8/6.1
	0/0.1
·IATA	
· Class · Label	8 Corrosive substances. 8 (6.1)
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Segregation groups Stowage Category Stowage Code 	Warning: Corrosive substances. 86 F-A,S-B (SGG18) Alkalis, (SGG6) cyanides B SW2 Clear of living quarters.
· 14.7 Maritime transport in bulk according to IM instruments	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IATA	
	(Contd. on page 12)



Printing date: 14.12.2022 Version number 9 (replaces version 8) Revision: 14.12.2022

Trade name: Brightener A for SCANDIA 360 Glanzzusatz A für SCANDIA 360

	(Contd. of page 11)
· Remarks:	24h emergency contact - (Dangerous goods emergency number)
	+49 172 739 6970
· UN "Model Regulation":	UN 2922 CORROSIVE LIQUID, TOXIC, N.O.S. (POTASSIUM HYDROXIDE, POTASSIUM CYANIDE), 8 (6.1), III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

· GADSL - Global Automotive Declarable Substance List

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category H2 ACUTE TOXIC
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 20 t
- · National regulations:
- · Waterhazard class: .
- · Other regulations, limitations and prohibitive regulations -
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Reasons for revise

If necessary, this saftey data sheet can revised according to legal guidelines.

Our current version for your reference is available on our website www.heimerle-meule.com

· Relevant phrases

H290 May be corrosive to metals.

H300 Fatal if swallowed.

H302 Harmful if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H330 Fatal if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

(Contd. on page 13)



Version number 9 (replaces version 8) Revision: 14.12.2022 Printing date: 14.12.2022

Trade name: Brightener A for SCANDIA 360 Glanzzusatz A für SCANDIA 360

(Contd. of page 12)

H400Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH032 Contact with acids liberates very toxic gas.

· Department issuing SDS:

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt Department BASU - Construction / Occupational Safety / Environment

sds@heimerle-meule.com

· Contact:

Herr Thomas Knuth

thomas.knuth@heimerle-meule.com

sds@heimerle-meule.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

AwSV: Ordinance on facilities for handling water-polluting substances (German regulation).

TRGS: Technical rules for hazardous substances (German regulation)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Met. Corr.1: Corrosive to metals - Category 1

Acute Tox. 1: Acute toxicity - Category 1

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.