

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.12.2022

Version number 2 (replaces version 1)

Revision: 21.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** Conducting silver-lacquer for airbrush
Silberleitlack - Airbrush

· **Article number:** 77953409

· **UFI:** QQM8-90XC-N00V-CQ8Y

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
Not approved for private consumers.

· **Application of the substance / the mixture** Lacquer

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Heimerle + Meule GmbH
Dennigstrasse 16
D-75179 Pforzheim

Telefon +49 (0) 7231 940-0
Telefax +49 (0) 7231 940-2199
www.heimerle-meule.com

· **Further information obtainable from:**

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt
Department BASU - Construction / Occupational Safety / Environment
sds@heimerle-meule.com

IATA - 24h Emergency Contact - IATA - 24h Emergency Contact -
(Dangerous goods emergency number)
+49 172 739 6970

· **1.4 Emergency telephone number:**

DEUTSCHLAND - GERMANY:
Vergiftungs-Informationen-Zentrale Freiburg, ++49 761 19240 (24 h)
(Poisoning Information Center)

GREAT BRITAIN:

National Poisons Information Service +44 121 507 4123
Members of the public seeking specific information on poisons should contact:
In England and Wales: NHS 111 - dial 111 - In Scotland: NHS 24 - dial 111

IRELAND

+353 1 809 2166 (7 Days 8 am -10 pm)
Healthcare Professionals: +353 1 809 2566

ITALY:

Istituto Superiore di Sanità (ISS) +3906499906140
Centro Antiveleni

Bergamo: +39 800 883300

Firenze +39 055 794 7819

Milano: +39 055 794 7819

Roma +39 06 68593726

Roma +39 06 49978000

Roma +39 06 3954343

KROATIA - REPUBLIKA HRVATSKA:

(+385) 01 2348 342

ESTLAND - ESTONIA:

Tervisemeti Mürgistusteabekeskuse

National (24/7): 16662

(+372) 7943 794

LETTLAND - LATVIA:

Valsts Toksikoloģijas centrs, Saindēšanās un zāļu informācijas centrs,

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.12.2022

Version number 2 (replaces version 1)

Revision: 21.12.2022

Trade name: Conducting silver-lacquer for airbrush
Silberleitlack - Airbrush

(Contd. of page 1)

(24h) 112

(24h) +371 67042473

LITAUEN - LIETUVOS RESPUBLIKA:

Poison Information Bureau (24/7), Tel.: +8 5 236 20 52

Apsinuodijimų informacijos biuras

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



environment

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



GHS02



GHS07



GHS09

- Signal word *Danger*
- Hazard-determining components of labelling:
1-methoxy-2-propanol
ethyl acetate
- Hazard statements
H225 Highly flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H410 Very toxic to aquatic life with long lasting effects.
- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.12.2022

Version number 2 (replaces version 1)

Revision: 21.12.2022

Trade name: Conducting silver-lacquer for airbrush
Silberleitlack - Airbrush

(Contd. of page 2)

- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
 P273 Avoid release to the environment.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components / Information on ingredients:**

CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 RTECS: UB 7700000	1-methoxy-2-propanol; monopropylene glycol methyl ether; 1-Methoxypropan-2-ol; 1-Methoxy-2-hydroxypropane; 2-Propanol, 1-methoxy-; Methoxyisopropanol; Propylene glycol monomethyl ether ----- ☠ Flam. Liq. 3, H226 ☠ Acute Tox. 3, H331 ☠ STOT SE 3, H336	50–100%
CAS: 7440-22-4 EINECS: 231-131-3	Silver (Powder <1mm); silver < 1mm particle size; silver; Silver (Powder <0.0001mm); Nano silver as per EU recommended definition ----- ☠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	25–50%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 RTECS: AH 5425000 Reg.nr.: 01-2119475103-46	ethyl acetate; Acetic acid, ethyl ester; Acetic ether; Ethyl ethanoate; Vinegar naphtha ----- ☠ Flam. Liq. 2, H225 ☠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	2.5–7%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Personal protection for the First Aider.
Take affected persons out of danger area and lay down.
Involve doctor immediately after a accident or unwell
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately rinse with water.
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:**
Drink plenty of water and provide fresh air. Call for a doctor immediately.
A person vomiting while laying on their back should be turned onto their side.
Rinse out mouth and then drink plenty of water.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.12.2022

Version number 2 (replaces version 1)

Revision: 21.12.2022

Trade name: Conducting silver-lacquer for airbrush
Silberleitlack - Airbrush

(Contd. of page 3)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Carbon monoxide (CO), Carbon dioxide (CO₂)
Nitrogen oxides (NO_x)
- **5.3 Advice for firefighters**
- **Protective equipment:**



Wear self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire

- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Use respiratory protective device against the effects of fumes/dust/aerosol.
Only handle and refill product in closed systems.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep receptacles tightly sealed.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.12.2022

Version number 2 (replaces version 1)

Revision: 21.12.2022

Trade name: Conducting silver-lacquer for airbrush
Silberleitlack - Airbrush

(Contd. of page 4)

Ensure good ventilation/exhaustion at the workplace.
The usual precautionary measures are to be adhered to when handling chemicals.
Prevent formation of aerosols.
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
Do not dry clean dust covered objects and floors. Wash thoroughly with plenty of water.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.
Observe official regulations on storing packagings .
Observe official regulations on storing packagings .
Prevent any seepage into the ground.

· **Information about storage in one common storage facility:** Store away from foodstuffs.

· **Further information about storage conditions:**

Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Store under lock and key and out of the reach of children.

· **Storage class:** 3

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 107-98-2 1-methoxy-2-propanol

WEL (Great Britain)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Sk
IOELV (European Union)	Short-term value: 568 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Skin
AGW (Germany)	Long-term value: 370 mg/m ³ , 100 ppm 2(I);DFG, EU, Y

CAS: 141-78-6 ethyl acetate

WEL (Great Britain)	Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm
IOELV (European Union)	Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm
AGW (Germany)	Long-term value: 730 mg/m ³ , 200 ppm 2(I);DFG, EU, Y

· **Regulatory information**

WEL (Great Britain): EH40/2020
IOELV (European Union): (EU) 2019/1831
AGW (Germany): TRGS 900

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.12.2022

Version number 2 (replaces version 1)

Revision: 21.12.2022

Trade name: Conducting silver-lacquer for airbrush
Silberleitlack - Airbrush

(Contd. of page 5)

· **Ingredients with biological limit values:**

CAS: 107-98-2 1-methoxy-2-propanol

BGW (Germany) 15 mg/l

Untersuchungsmaterial: Urin

Probennahmezeitpunkt: Expositionsende bzw. Schichtende

Parameter: 1-Methoxypropan-2-ol

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

According to EC Directive 89/686/EEC

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire.

according EN 14387

according to EN 143

· **Hand protection**



Protective gloves

according to EN 374

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

Sensibilisation by the components in the glove materials is possible.

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Prior to working with gloves the rubbing in with tanniferous skin-protecting agents for the avoidance of skin softening due to perspiration is recommended.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 3).

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.12.2022

Version number 2 (replaces version 1)

Revision: 21.12.2022

Trade name: Conducting silver-lacquer for airbrush
Silberleitlack - Airbrush

(Contd. of page 6)

Value for the permeation: Level ≤ 3 · **Not suitable are gloves made of the following materials:**

Leather gloves

Strong material gloves

· **Eye/face protection**

Tightly sealed goggles

according to EN 166

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

· **Colour:**

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

Undetermined.

· **Flammability**

Highly flammable.

· **Lower and upper explosion limit**· **Lower:**

2.3 Vol % (CAS: 107-98-2 1-methoxy-2-propanol)

· **Upper:**

~20 Vol % (CAS: 107-98-2 1-methoxy-2-propanol)

· **Flash point:**

< 23°C (< 73.4°F)

· **Ignition temperature:**

< 300°C (< 572°F)

· **Decomposition temperature:**

Not determined.

· **pH**

Mixture is non-polar/aprotic.

· **Viscosity:**· **Kinematic viscosity**

Not determined.

· **Dynamic:**

Not determined.

· **Solubility**· **water:**

Fully miscible.

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Vapour pressure:**

Not determined.

· **Density and/or relative density**· **Density:**

Not determined.

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **9.2 Other information**

< 75.00 %

· **Appearance:**· **Form:**

Fluid

· **Important information on protection of health and environment, and on safety.**· **Auto-ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.12.2022

Version number 2 (replaces version 1)

Revision: 21.12.2022

Trade name: Conducting silver-lacquer for airbrush
Silberleitlack - Airbrush

(Contd. of page 7)

· Solvent content:	
· Organic solvents:	<75.0 %
· Solids content:	30.0 %
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with acids, alkalis and oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**

· **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Inhalative	LC50/4 h	>8.57 mg/l (rat)
------------	----------	------------------

CAS: 107-98-2 1-methoxy-2-propanol

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	13,500 mg/kg (rbt)
Inhalative	LC50/4 h	6 mg/l (rat)

CAS: 141-78-6 ethyl acetate

Oral	LD50	4,935 mg/kg (rbt)
Inhalative	LC50/4 h	1,600 mg/l (rat)

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.12.2022

Version number 2 (replaces version 1)

Revision: 21.12.2022

Trade name: Conducting silver-lacquer for airbrush
Silberleitlack - Airbrush

(Contd. of page 8)

- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

- **Aquatic toxicity:**

CAS: 7440-22-4 Silver (Powder <Imm)


(Chronische) aquatische Toxizität | 0.0008 mg/l (aquatic invertebrates)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment** Not applicable.
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

- **Recommendation**



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

- **Waste disposal key:**

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

- **Uncleaned packaging:**

- **Recommendation:**

Disposal must be made according to official regulations.

Packaging which is uncleaned or soiled with product remains is to be treated like the product itself

Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish

- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

GB

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.12.2022

Version number 2 (replaces version 1)

Revision: 21.12.2022

Trade name: Conducting silver-lacquer for airbrush
Silberleitlack - Airbrush

(Contd. of page 9)

SECTION 14: Transport information

· 14.1 UN number or ID number
· ADR, IMDG, IATA

UN1263


· 14.2 UN proper shipping name
· ADR

UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS,
special provision 640D
PAINT

· IMDG, IATA

· 14.3 Transport hazard class(es)

· ADR



· Class
· Label

3 Flammable liquids.
3

· IMDG, IATA



· Class
· Label

3 Flammable liquids.
3

· 14.4 Packing group
· ADR, IMDG, IATA

II

· 14.5 Environmental hazards:
· Special marking (ADR):

Symbol (fish and tree)

· 14.6 Special precautions for user
· Hazard identification number (Kemler code):
· EMS Number:
· Stowage Category

Warning: Flammable liquids.
33
F-E,S-E
B

· 14.7 Maritime transport in bulk according to IMO
instruments

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)
· Excepted quantities (EQ)

5L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· Transport category

2

· IMDG

· Limited quantities (LQ)
· Excepted quantities (EQ)

5L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.12.2022

Version number 2 (replaces version 1)

Revision: 21.12.2022

Trade name: Conducting silver-lacquer for airbrush
Silberleitlack - Airbrush

(Contd. of page 10)

· **IATA**· **Remarks:**

24h emergency contact -
(Dangerous goods emergency number)

+49 172 739 6970

· **UN "Model Regulation":**

UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II,
ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

· **GADSL - Global Automotive Declarable Substance List**

CAS: 7440-22-4 | Silver (Powder <1mm)

D/P(LR)

· **Directive 2012/18/EU**· **Named dangerous substances - ANNEX I** None of the ingredients is listed.· **Seveso category**

E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t· **National regulations:**· **Technical instructions (air):**

Class	Share in %
NK	50–100

· **Waterhazard class:** .· **Other regulations, limitations and prohibitive regulations -**· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Reasons for revise**

If necessary, this safety data sheet can revised according to legal guidelines.

Our current version for your reference is available on our website
www.heimerle-meule.com

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.12.2022

Version number 2 (replaces version 1)

Revision: 21.12.2022

Trade name: Conducting silver-lacquer for airbrush
Silberleitlack - Airbrush

(Contd. of page 11)

· **Relevant phrases**

- H225 *Highly flammable liquid and vapour.*
- H226 *Flammable liquid and vapour.*
- H319 *Causes serious eye irritation.*
- H331 *Toxic if inhaled.*
- H336 *May cause drowsiness or dizziness.*
- H400 *Very toxic to aquatic life.*
- H410 *Very toxic to aquatic life with long lasting effects.*
- EUH066 *Repeated exposure may cause skin dryness or cracking.*

· **Department issuing SDS:**

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt
Department BASU - Construction / Occupational Safety / Environment

sds@heimerle-meule.com

· **Contact:**

Herr Thomas Knuth
thomas.knuth@heimerle-meule.com
sds@heimerle-meule.com

· **Abbreviations and acronyms:**

- AwSV: Ordinance on facilities for handling water-polluting substances (German regulation).*
- TRGS: Technical rules for hazardous substances (German regulation)*
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*
- IMDG: International Maritime Code for Dangerous Goods*
- IATA: International Air Transport Association*
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals*
- EINECS: European Inventory of Existing Commercial Chemical Substances*
- ELINCS: European List of Notified Chemical Substances*
- CAS: Chemical Abstracts Service (division of the American Chemical Society)*
- LC50: Lethal concentration, 50 percent*
- LD50: Lethal dose, 50 percent*
- PBT: Persistent, Bioaccumulative and Toxic*
- vPvB: very Persistent and very Bioaccumulative*
- Flam. Liq. 2: Flammable liquids – Category 2*
- Flam. Liq. 3: Flammable liquids – Category 3*
- Acute Tox. 3: Acute toxicity – Category 3*
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1*
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*

· *** Data compared to the previous version altered.**