

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 09.09.2020

Version number 2

Revision: _____ 09.09.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** Conducting solution GP 205 L

Leitsalzlösung GP 205 L

· **Article number:** 86938481

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
Not approved for private consumers.

· **Application of the substance / the mixture** Galvanic bath

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Heimerle + Meule GmbH
Dennigstrasse 16
D-75179 Pforzheim

Telefon +49 (0) 7231 940-0
Telefax +49 (0) 7231 940-2199
www.heimerle-meule.com

· **Further information obtainable from:**

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt
Department BASU - Construction / Occupational Safety / Environment
sds@heimerle-meule.com

IATA - 24h Emergency Contact - IATA - 24h Emergency Contact -
(Dangerous goods emergency number)
+49 172 739 6970

· **1.4 Emergency telephone number:**

DEUTSCHLAND - GERMANY:

Vergiftungs-Informationen-Zentrale Freiburg, ++49 761 19240 (24 h)
(Poisoning Information Center)

GREAT BRITAIN:

National Poisons Information Service +44 121 507 4123

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111 - In Scotland: NHS 24 - dial 111

ITALY:

Istituto Superiore di Sanità +3906499906140

KROATIA - REPUBLIKA HRVATSKA:

(+385) 01 2348 342

ESTLAND - ESTONIA:

Tervisemeti Mürgistusteabekeskuse 16662, (+342) 7914 794

LETTLAND - LATVIA:

Latvijas Vides, ģeoloģijas un meteoroloģijas centrs (+371) 670 32600

LITAUEN - LIETUVOS RESPUBLIKA:

Apsinuodijimų informacijos biuras +370 (85) 2362052

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 09.09.2020

Version number 2

Revision: _____ 09.09.2020

Trade name: Conducting solution GP 205 L
Leitsalzlösung GP 205 L

(Contd. of page 1)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

- | | | |
|-----------|-------|---|
| Carc. 1A | H350i | May cause cancer by inhalation. |
| Repr. 1B | H360D | May damage the unborn child. |
| STOT RE 2 | H373 | May cause damage to the respiratory system and the male genitalia through prolonged or repeated exposure. |



GHS07

- | | | |
|-------------------|------|--|
| Eye Irrit. 2 | H319 | Causes serious eye irritation. |
| Skin Sens. 1 | H317 | May cause an allergic skin reaction. |
| Aquatic Chronic 3 | H412 | Harmful to aquatic life with long lasting effects. |

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS07



GHS08

- Signal word *Danger*
- Hazard-determining components of labelling:
nickel sulphate
- Hazard statements

H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H350i	May cause cancer by inhalation.
H360D	May damage the unborn child.
H373	May cause damage to the respiratory system and the male genitalia through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
- Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 09.09.2020

Version number 2

Revision: _____ 09.09.2020

Trade name: Conducting solution GP 205 L
Leitsalzlösung GP 205 L

(Contd. of page 2)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

Restricted to professional users.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components / Information on ingredients:**

CAS: 10043-35-3 EINECS: 233-139-2 Index number: 005-007-00-2 RTECS: ED 4550000 Reg.nr.: 01-2119486683-25	boric acid; boric acid, crude natural, containing not more than 85 per cent of H ₃ BO ₃ calculated on the dry weight ----- Repr. 1B, H360FD Specific concentration limit: Repr. 1B; H360: C ≥ 5.5 %	1–2.5%
CAS: 64-02-8 EINECS: 200-573-9 Index number: 607-428-00-2 RTECS: AH 5075000	tetrasodium ethylenediaminetetraacetate ----- STOT RE 2, H373 Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H332	1%
CAS: 7786-81-4 EINECS: 232-104-9 Index number: 028-009-00-5	nickel sulphate; nickel sulfate ----- Resp. Sens. 1, H334; Muta. 2, H341; Carc. 1A, H350i; Repr. 1B, H360D; STOT RE 1, H372 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limits: STOT RE 1; H372: C ≥ 1 % STOT RE 2; H373: 0.1 % ≤ C < 1 % Skin Irrit. 2; H315: C ≥ 20 % Skin Sens. 1; H317: C ≥ 0.01 %	≥0.5–<1%

· **SVHC**

CAS: 10043-35-3 | boric acid

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

Involve doctor immediately after an accident or unwell

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 09.09.2020

Version number 2

Revision: _____ 09.09.2020

Trade name: Conducting solution GP 205 L
Leitsalzlösung GP 205 L

(Contd. of page 3)

- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Drink plenty of water and provide fresh air. Call for a doctor immediately.
A person vomiting while laying on their back should be turned onto their side.
Rinse out mouth and then drink plenty of water.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Mount respiratory protective device.



Wear self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire

- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Use respiratory protective device against the effects of fumes/dust/aerosol.
Only handle and refill product in closed systems.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 09.09.2020

Version number 2

Revision: _____ 09.09.2020

Trade name: Conducting solution GP 205 L
Leitsalzlösung GP 205 L

(Contd. of page 4)

- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep receptacles tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
The usual precautionary measures are to be adhered to when handling chemicals.
Prevent formation of aerosols.
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
Do not dry clean dust covered objects and floors. Wash thoroughly with plenty of water.
- **Information about fire - and explosion protection:** Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings .
Observe official regulations on storing packagings .
Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 6.1 D
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 10043-35-3 boric acid

AGW (Germany)	Long-term value: 0.5* mg/m ³ 2(I);*einateambar; AGS, Y, 10
---------------	--

CAS: 7786-81-4 nickel sulphate

WEL (Great Britain)	Long-term value: 0.1 mg/m ³ as Ni; Sk; Carc; Sen
AGW (Germany)	Long-term value: 0.030E mg/m ³ 8(II);AGS, Sh, Y, 10, 24, 31
TRGS 910 (Germany)	Short-term value: 0.006 (A) mg/m ³ Long-term value: 0.006 (A) mg/m ³ 8, Konzentrationen beziehen sich auf Ni-Gehalt

- **Regulatory information**
AGW (Germany): TRGS 900
WEL (Great Britain): EH40/2020
- **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 6)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 09.09.2020

Version number 2

Revision: _____ 09.09.2020

Trade name: Conducting solution GP 205 L
Leitsalzlösung GP 205 L

(Contd. of page 5)

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

According to EC Directive 89/686/EEC

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire.

according EN 14387

according to EN 143

· **Protection of hands:**



Protective gloves

according to EN 374

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

Sensibilisation by the components in the glove materials is possible.

Check the permeability prior to each anewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Prior to working with gloves the rubbing in with tanniferous skin-protecting agents for the avoidance of skin softening due to perspiration is recommended.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 3).

Value for the permeation: Level ≤ 3

· **Not suitable are gloves made of the following materials:**

Leather gloves

Strong material gloves

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 09.09.2020

Version number 2

Revision: _____ 09.09.2020

Trade name: Conducting solution GP 205 L
Leitsalzlösung GP 205 L

(Contd. of page 6)

· **Eye protection:**

Tightly sealed goggles

according to EN 166

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

· Form:	Fluid
· Colour:	Light blue
· Odour:	Recognisable
· Odour threshold:	Not determined.

· **pH-value at 20°C (68°F):** 4· **Change in condition**

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	>100°C (>212°F)

· **Flash point:** Not applicable.· **Flammability (solid, gas):** Not applicable.· **Decomposition temperature:** Not determined.· **Auto-ignition temperature:** Product is not selfigniting.· **Explosive properties:** Product does not present an explosion hazard.· **Explosion limits:**

· Lower:	Not determined.
· Upper:	Not determined.

· **Vapour pressure:** Not determined.· **Density:** Not determined.· **Relative density** Not determined.· **Vapour density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with water:**

Fully miscible.

· **Partition coefficient: n-octanol/water:** Not determined.· **Viscosity:**· **Dynamic:** Not determined.· **Kinematic:** Not determined.· **9.2 Other information** 0.00 %

GB

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 09.09.2020

Version number 2

Revision: _____ 09.09.2020

Trade name: Conducting solution GP 205 L
Leitsalzlösung GP 205 L

(Contd. of page 7)

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with acids, alkalis and oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	50,000 mg/kg
Inhalative	LC50/4 h	1,100 mg/l

CAS: 10043-35-3 boric acid

Oral	LD50	2,660 mg/kg (rat)
------	------	-------------------

CAS: 64-02-8 tetrasodium ethylenediaminetetraacetate

Oral	LD50	500 mg/kg (ATE)
Inhalative	LC50/4 h	11 mg/l (ATE)

CAS: 7786-81-4 nickel sulphate

Oral	LD50	500 mg/kg (ATE)
Inhalative	LC50/4 h	1.5 mg/l (ATE)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity**
May cause cancer by inhalation.
- **Reproductive toxicity**
May damage the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
May cause damage to the respiratory system and the male genitalia through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 09.09.2020

Version number 2

Revision: _____ 09.09.2020


Trade name: Conducting solution GP 205 L
Leitsalzlösung GP 205 L

(Contd. of page 8)

- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment** Not applicable.
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

- **Waste disposal key:**
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.
- **European waste catalogue**
There are no uniform EC regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding laws and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste

11 00 00	WASTES FROM CHEMICAL SURFACE TREATMENT AND COATING OF METALS AND OTHER MATERIALS; NON-FERROUS HYDRO-METALLURGY
11 01 00	wastes from chemical surface treatment and coating of metals and other materials (for example galvanic processes, zinc coating processes, pickling processes, etching, phosphating, alkaline degreasing, anodising)
11 01 98*	other wastes containing hazardous substances
HP7	Carcinogenic
HP10	Toxic for reproduction
HP14	Ecotoxic

- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Packaging which is uncleaned or soiled with product remains is to be treated like the product itself
Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

GB

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 09.09.2020



Version number 2

Revision: _____ 09.09.2020

Trade name: Conducting solution GP 205 L
Leitsalzlösung GP 205 L

(Contd. of page 9)

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN3082
· 14.2 UN proper shipping name · ADR · IMDG · IATA	UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (nickel sulphate) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (nickel sulphate), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (nickel sulphate)
· 14.3 Transport hazard class(es) · ADR, IMDG, IATA	
 	
· Class · Label	9 Miscellaneous dangerous substances and articles. 9
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): · Special marking (IATA):	Product contains environmentally hazardous substances: nickel sulphate Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	3 -
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IATA · Remarks:	24h emergency contact -

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 09.09.2020

Version number 2

Revision: _____ 09.09.2020

Trade name: Conducting solution GP 205 L
Leitsalzlösung GP 205 L

(Contd. of page 10)

(Dangerous goods emergency number)

+49 172 739 6970

· **UN "Model Regulation":** UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (NICKEL SULPHATE), 9, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **GADSL - Global Automotive Declarable Substance List**

CAS: 10043-35-3	boric acid	D/P(LR)
CAS: 7786-81-4	nickel sulphate	D(FI)

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 27, 28, 30

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

Employment restrictions concerning women of child-bearing age must be observed.

· **Technical instructions (air):**

Class	Share in %
II	0.9

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

· **Other regulations, limitations and prohibitive regulations -**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

CAS: 10043-35-3	boric acid
-----------------	------------

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 09.09.2020

Version number 2

Revision: _____ 09.09.2020

Trade name: Conducting solution GP 205 L
Leitsalzlösung GP 205 L

(Contd. of page 11)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Reasons for revise**

If necessary, this safety data sheet can be revised according to legal guidelines.

Our current version for your reference is available on our website

www.heimerle-meule.com

· **Date from last issue** : 30.09.2019

· **Relevant phrases**

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H341 Suspected of causing genetic defects.

H350i May cause cancer by inhalation.

H360D May damage the unborn child.

H360FD May damage fertility. May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to the respiratory system and the male genitalia through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· **Department issuing SDS:**

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt

Department BASU - Construction / Occupational Safety / Environment

sds@heimerle-meule.com

· **Contact:**

Herr Thomas Knuth

Knuth@heimerle-meule.com

sds@heimerle-meule.com

· **Abbreviations and acronyms:**

AwSV: Ordinance on facilities for handling water-polluting substances (German regulation).

TRGS: Technical rules for hazardous substances (German regulation)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - oral - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 09.09.2020

Version number 2

Revision: _____ 09.09.2020

Trade name: Conducting solution GP 205 L
Leitsalzlösung GP 205 L

(Contd. of page 12)

*Skin Sens. 1: Skin sensitisation – Category 1**Muta. 2: Germ cell mutagenicity – Category 2**Carc. 1A: Carcinogenicity – Category 1Ai**Repr. 1B: Reproductive toxicity – Category 1B**Repr. 1B: Reproductive toxicity – Category 1B**STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

· *** Data compared to the previous version altered.**

GB