

Revision: 14.12.2022

Printing date: 14.12.2022 Version number 14 (replaces version 13)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Covering lacquer blue Abdecklack Blau

• Article number: 81010567 81010568

- 1.2 Relevant identified uses of the substance or mixture and uses advised against Not approved for private consumers.
- · Application of the substance / the mixture Masking material
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Heimerle + Meule GmbH Dennigstrasse 16 D-75179 Pforzheim

Telefon +49 (0) 7231 940-0 Telefax +49 (0) 7231 940-2199 www.heimerle-meule.com

· Further information obtainable from:

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt Department BASU - Construction / Occupational Safety / Environment sds@heimerle-meule.com

IATA - 24h Emergency Contact - IATA - 24h Emergency Contact - (Dangerous goods emergency number) +49 172 739 6970

· 1.4 Emergency telephone number:

DEUTSCHLAND - GERMANY:

Vergiftungs-Informations-Zentrale Freiburg, ++49 761 19240 (24 h)

(Poisoning Information Center)

GREAT BRITAIN:

National Poisons Information Service +44 121 507 4123

Members of the public seeking specific information on poisons should contact: In England and Wales: NHS 111 - dial 111 - In Scotland: NHS 24 - dial 111

IRELAND

+353 1 809 2166 (7 Days 8 am -10 pm)

Healthcare Professionals: +353 1 809 2566

ITALY:

Istituto Superiore di Sanità (ISS) +3906499906140

Centro Antiveleni

Bergamo: +39 800 883300 Firenze +39 055 794 7819 Milano: +39 055 794 7819 Roma +39 06 68593726 Roma +39 06 49978000

Roma +39 06 3954343

KROATIA - REPUBLIKA HRVATSKA:

(+385) 01 2348 342 ESTLAND - ESTONIA:

Tervisemeti Mürgistusteabekeskuse

National (24/7): 16662

(Contd. on page 2)



Printing date: 14.12.2022 Version number 14 (replaces version 13) Revision: 14.12.2022

Trade name: Covering lacquer blue Abdecklack Blau

(Contd. of page 1)

(+372) 7943 794

LETTLAND - LATVIA:

Valsts Toksikoloģijas centrs, Saindēšanās un zāļu informācijas centrs,

(24h) 112

(24h) +371 67042473

LITAUEN - LIETUVOS RESPUBLIKA:

Poison Information Bureau (24/7), Tel.: +8 5 236 20 52

Apsinuodijimų informacijos biuras

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



STOT SE 3

H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS07

GHS09

- · Signal word Warning
- · Hazard-determining components of labelling:

Solvent naphtha (petroleum), heavy arom.

· Hazard statements

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 3)



Printing date: 14.12.2022 Version number 14 (replaces version 13) Revision: 14.12.2022

Trade name: Covering lacquer blue Abdecklack Blau

(Contd. of page 2)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components / Information on ingredients:		
CAS: 64742-94-5 EINECS: 265-198-5	Solvent naphtha (petroleum), heavy arom. Asp. Tox. 1, H304	≥25-≤50%
EINECS: 265-198-5 Index number: 649-424-00-3	Aquatic Chronic 2, H411 STOT SE 3, H336	
CAS: 56-81-5 EINECS: 200-289-5 RTECS: MA 8050000	glycerol; Glycerine; 1,2,3-Propanetriol; Trihydroxypropane; Emery 918; OPTIM Glycerine 99.7% USP; Glycyl alcohol; Concentrated glycerine; 1,2,3-Trihydroxypropane substance with a Community workplace exposure limit	

· Additional information:

contains less than 0.1% benzene (EINECS No 200-753-7). For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

Involve doctor immediately after a accident or unwell

- · After inhalation: Seek medical treatment in case of complaints.
- · After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing:

Drink plenty of water and provide fresh air. Call for a doctor immediately.

A person vomiting while laying on their back should be turned onto their side.

Rinse out mouth and then drink plenty of water.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Carbon monoxide (CO), Carbon dioxide (CO2)

(Contd. on page 4)

Heimerle + Meule

Revision: 14.12.2022

Printing date: 14.12.2022 Version number 14 (replaces version 13)

Trade name: Covering lacquer blue Abdecklack Blau

(Contd. of page 3)

· 5.3 Advice for firefighters

· Protective equipment:

Do not inhale explosion gases or combustion gases.



Wear self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire

· Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Only handle and refill product in closed systems.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

he usual precautionary measures are to be adhered to when handling chemicals.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not dry clean dust covered objects and floors. Wash thoroughly with plenty of water.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Fumes can combine with air to form an explosive mixture.

(Contd. on page 5)

Heimerle + Meule

Printing date: 14.12.2022 Version number 14 (replaces version 13) Revision: 14.12.2022

Trade name: Covering lacquer blue Abdecklack Blau

(Contd. of page 4)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings.

Observe official regulations on storing packagings.

Prevent any seepage into the ground.

Information about storage in one common storage facility:

Do not store together with materials which also support fire

Store away from foodstuffs.

- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:		
CAS: 56-81-5 glycerol		
WEL (Great Britain)	Long-term value: 10 mg/m³	
	Long-term value: 200 E mg/m³ 2 (I);DFG, Y	

Regulatory information

WEL (Great Britain): EH40/2020 AGW (Germany): TRGS 900

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

According to EC Directive 89/686/EEC

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device only when aerosol or mist is formed.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire.

according EN 14387

according to EN 143

• Recommended filter device for short term use: Combination filter A-P2

· Hand protection

Solvent resistant gloves

Check protective gloves prior to each use for their proper condition.

according to EN 374

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

Sensibilisation by the components in the glove materials is possible.

(Contd. on page 6)



Printing date: 14.12.2022 Version number 14 (replaces version 13) Revision: 14.12.2022

Trade name: Covering lacquer blue Abdecklack Blau

(Contd. of page 5)

Check the permeability prior to each anewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Prior to working with gloves the rubbing in with tanniferous skin-protecting agents for the avoidance of skin softening due to perspiration is recommended.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

- · Eye/face protection Goggles recommended during refilling
- · **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state Colour: Blue

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range Undetermined.
• Flammability Not applicable.

· Lower and upper explosion limit

· Lower: 0.8 Vol % *· Upper:* 7 Vol %

Flash point: > 60°C (> 140°F) (DIN 51755)
 Ignition temperature: 400°C (752°F) (DIN 51794)

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

• Kinematic viscosity
• Dynamic at 20°C (68°F):

Not determined.
16,000 mPas

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20°C (68°F): <1 hPa (<0.8 mm Hg)

· Density and/or relative density

• **Density at 20°C (68°F):** 1.06 g/cm³ (8.85 lbs/gal)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Viscous

(Contd. on page 7)



Printing date: 14.12.2022 Version number 14 (replaces version 13) Revision: 14.12.2022

Trade name: Covering lacquer blue Abdecklack Blau

	(Contd. of page 6)	
Important information on protection of health a	nd	
environment, and on safety.		
· Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product does not present an explosion hazard.	
· Change in condition		
Evaporation rate	Not determined.	
· Information with regard to physical hazard classes		
· Explosives	Void	
· Flammable gases	Void	
· Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
· Flammable liquids	Void	
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flammable	,	
gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability

· Corrosive to metals · Desensitised explosives

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Void

Void

· 10.3 Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Reacts with acids, alkalis and oxidising agents.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

ſ	LD/LC50 values relevant for classification:		
f	CAS: 56-81-5 glycerol		
Ī	Oral	LD50	12,600 mg/kg (Rat)
	Dermal	LD50	10,000 mg/kg (Kanninchen)

- · STOT-single exposure May cause drowsiness or dizziness.
- · Subacute to chronic toxicity:

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

(Contd. on page 8)



Printing date: 14.12.2022 Version number 14 (replaces version 13) Revision: 14.12.2022

Trade name: Covering lacquer blue Abdecklack Blau

(Contd. of page 7)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment Not applicable.
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation





Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

· Waste disposal key:

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Packaging which is uncleaned or soiled with product remains is to be treated like the product itself Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish

GB



Printing date: 14.12.2022 Version number 14 (replaces version 13) Revision: 14.12.2022

Trade name: Covering lacquer blue Abdecklack Blau

(Contd. of page 8)

SECTION 14: Transport information	
14.1 UN number or ID number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR	UN3082 ENVIRONMENTALLY HAZARDOS SUBSTANCE, LIQUID, N.O.S. (Solvent napht
IMDG	(petroleum), heavy arom.) ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (Solvent naphtha (petroleum), hea arom.), MARINE POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (Solvent naphtha (petroleum), hea arom.)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	9 Miscellaneous dangerous substances and articles.9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	Yes
танне рошини.	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances as articles.
Hazard identification number (Kemler code):	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk according to IM instruments	10 Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
Transport category	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3
IMDG Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
1	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)



Printing date: 14.12.2022 Version number 14 (replaces version 13) Revision: 14.12.2022

Trade name: Covering lacquer blue Abdecklack Blau

	(Contd. of page 9)
· IATA · Remarks:	
	24h emergency contact - (Dangerous goods emergency number)
	+49 172 739 6970
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM.), 9, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

· GADSL - Global Automotive Declarable Substance List

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	25-50

- · Waterhazard class: .
- · Other regulations, limitations and prohibitive regulations -
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Reasons for revise

If necessary, this saftey data sheet can revised according to legal guidelines.

Our current version for your reference is available on our website www.heimerle-meule.com

· Relevant phrases

H304 May be fatal if swallowed and enters airways.

(Contd. on page 11)



Printing date: 14.12.2022 Version number 14 (replaces version 13) Revision: 14.12.2022

Trade name: Covering lacquer blue Abdecklack Blau

(Contd. of page 10)

H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS:

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt Department BASU - Construction / Occupational Safety / Environment

sds@heimerle-meule.com

· Contact:

Herr Thomas Knuth

thomas.knuth@heimerle-meule.com

sds@heimerle-meule.com

· Abbreviations and acronyms:

AwSV: Ordinance on facilities for handling water-polluting substances (German regulation).

TRGS: Technical rules for hazardous substances (German regulation)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* * Data compared to the previous version altered.

GR -