

Printing date: 19.10.2023 Version number 3 (replaces version 2) Revision: 19.10.2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: ECOLYT SG 200

· Article number:

77953443 = 8g Au/ 500ml 77953444 = 16g Au/1000ml

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Not approved for private consumers.
- · Application of the substance / the mixture Galvanic bath
- 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Heimerle + Meule GmbH Dennigstrasse 16 D-75179 Pforzheim

Telefon +49 (0) 7231 940-0 Telefax +49 (0) 7231 940-2199 www.heimerle-meule.com

· Further information obtainable from:

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt Department BASU - Construction / Occupational Safety / Environment sds@heimerle-meule.com

IATA - 24h Emergency Contact - IATA - 24h Emergency Contact - (Dangerous goods emergency number) +49 172 739 6970

· 1.4 Emergency telephone number:

DEUTSCHLAND - GERMANY:

Vergiftungs-Informations-Zentrale Freiburg, ++49 761 19240 (24 h)

(Poisoning Information Center)

GREAT BRITAIN:

National Poisons Information Service +44 121 507 4123

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111 - In Scotland: NHS 24 - dial 111

*IRELAND* 

+353 1 809 2166 (7 Days 8 am -10 pm)

Healthcare Professionals: +353 1 809 2566

ITALY:

*Istituto Superiore di Sanità (ISS) +3906499906140* 

Centro Antiveleni

Bergamo: +39 800 883300

Firenze +39 055 794 7819

Milano: +39 055 794 7819

Roma +39 06 68593726 Roma +39 06 49978000

Roma +39 00 499/8000

Roma +39 06 3954343

KROATIA - REPUBLIKA HRVATSKA:

(+385) 01 2348 342

ESTLAND - ESTONIA:

Tervisemeti Mürgistusteabekeskuse

National (24/7): 16662

(+372) 7943 794

LETTLAND - LATVIA:

(Contd. on page 2)



Printing date: 19.10.2023 Version number 3 (replaces version 2) Revision: 19.10.2023

Trade name: ECOLYT SG 200

(Contd. of page 1)

Valsts Toksikoloģijas centrs, Saindēšanās un zāļu informācijas centrs,

(24h) 112

(24h) +371 67042473

LITAUEN - LIETUVOS RESPUBLIKA:

Poison Information Bureau (24/7), Tel.: +8 5 236 20 52

Apsinuodijimų informacijos biuras

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



- · Signal word Warning
- · Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

P264 Wash thoroughly after handling.P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P337+P313 If eye irritation persists: Get medical advice/attention.

· Additional information:

EUH031 Contact with acids liberates toxic gas.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



Printing date: 19.10.2023 Version number 3 (replaces version 2) Revision: 19.10.2023

Trade name: ECOLYT SG 200

		(Contd. of page 2)
· Dangerous components / Inf	formation on ingredients:	
CAS: 71662-32-3 EINECS: 275-798-9	Ammonium disulfito aurate (I) solution  Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 EUH031	≥1-≤7%
CAS: 7783-28-0 EINECS: 231-987-8 RTECS: TB 9375000	diammonium hydrogenorthophosphate  • Acute Tox. 4, H312; Acute Tox. 4, H332	2.5–7%
CAS: 7664-41-7 EINECS: 231-635-3 Index number: 007-001-00-5 RTECS: BO 0875000	ammonia, anhydrous; anhydrous ammonia; Ammonia Acute Tox. 3, H331 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Acute Tox. 4, H302 Flam. Gas 2, H221; Press. Gas (Comp.), H280 substance with a Community workplace exposure limit	≥0.1-<0.25%

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- · General information:

Take affected persons out into the fresh air.

Involve doctor immediately.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

Involve doctor immediately after a accident or unwell

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing:

Drink plenty of water and provide fresh air. Call for a doctor immediately.

A person vomiting while laying on their back should be turned onto their side.

Rinse out mouth and then drink plenty of water.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Sulphur dioxide (SO2)

Ammonia (NH 3)

Phosphorus oxides (P2Ox)

(Contd. on page 4)

Heimerle + Meule

Printing date: 19.10.2023 Version number 3 (replaces version 2) Revision: 19.10.2023

Trade name: ECOLYT SG 200

(Contd. of page 3)

#### · 5.3 Advice for firefighters

· Protective equipment:

Mount respiratory protective device.



Wear self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter the sewage system.

## SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

*Use respiratory protective device against the effects of fumes/dust/aerosol.* 

Only handle and refill product in closed systems.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

### · 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

he usual precautionary measures are to be adhered to when handling chemicals.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not dry clean dust covered objects and floors. Wash thoroughly with plenty of water.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings.

Observe official regulations on storing packagings .

Prevent any seepage into the ground.

· Information about storage in one common storage facility:

Do not store together with acids.

Store away from foodstuffs.

· Further information about storage conditions:

Protect from frost.

(Contd. on page 5)



Printing date: 19.10.2023 Version number 3 (replaces version 2) Revision: 19.10.2023

Trade name: ECOLYT SG 200

(Contd. of page 4)

Keep container tightly sealed.

· Storage class: 12

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

· Ingredients with limit	values that require monitoring at the workplace:
CAS: 7664-41-7 amm	onia, anhydrous
IOELV (European Un	ion) Short-term value: 36 mg/m³, 50 ppm Long-term value: 14 mg/m³, 20 ppm
AGW (Germany)	Long-term value: 14 mg/m³, 20 ppm 2(1);DFG, EU, Y
CAS: 1336-21-6 amm	onia
AGW (Germany)	Long-term value: 14 mg/m³, 20 ppm 2(1);DFG, EU, Y

#### · Regulatory information

IOELV (European Union): (EU) 2019/1831

AGW (Germany): TRGS 900

· Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

According to EC Directive 89/686/EEC

#### · Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device only when aerosol or mist is formed.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire.

according EN 14387

according to EN 143

### · Recommended filter device for short term use:

according to EN 14387/EN 143

Combination filter B-P2

#### · Hand protection

according to EN 374

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

Sensibilisation by the components in the glove materials is possible.

Check the permeability prior to each anewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Prior to working with gloves the rubbing in with tanniferous skin-protecting agents for the avoidance of skin softening due to perspiration is recommended.

#### · Material of gloves

Natural rubber, NR

Recommended thickness of the material:  $\geq 0.7$  mm

(Contd. on page 6)



Printing date: 19.10.2023 Version number 3 (replaces version 2) Revision: 19.10.2023

Trade name: ECOLYT SG 200

(Contd. of page 5)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

- · Eye/face protection Goggles recommended during refilling
- · Body protection: Protective work clothing

CECTION	0. D1	1 1 .1	
	y: Physical	and chemical	nvanevnes
DECITOI	> I Itypotetti	direct Circuit	properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:
Fluid
Colourless
Like ammoniac
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling

range ~100°C (~212°F)
• Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
 Upper: Not determined.
 Flash point: Not applicable.
 Decomposition temperature: Not determined.

• pH at 20°C (68°F) 8.8

· Viscosity:

Kinematic viscosity
 Dynamic:
 Not determined.
 Solubility

Solubility

water: Fully miscible.
 Partition coefficient n-octanol/water (log value)
 Vapour pressure: Not determined.

Density and/or relative density

• Density at 20°C (68°F): 1.07 g/cm³ (8.93 lbs/gal)

Relative densityVapour densityNot determined.Not determined.

• 9.2 Other information 0.00 %

· Appearance:

· Form: Fluid

· Important information on protection of health and

environment, and on safety.

• Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

· Solvent content:

• Water: 82.7 %
 • Solids content: 0.0 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void

(Contd. on page 7)



Printing date: 19.10.2023 Version number 3 (replaces version 2) Revision: 19.10.2023

Trade name: ECOLYT SG 200

		(Contd. of page 6
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

Reacts with acids, alkalis and oxidising agents.

Contact with acids releases toxic gases.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Acids
- · 10.6 Hazardous decomposition products:

Phosphorus oxides (e.g. P2O5)

Sulphur dioxide

Ammonia

## SECTION 11: Toxicological information

· LD/LC50 values relevant for classification:

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

		· · · · · · · · · · · · · · · · · · ·
ATE (Acu	te Toxicity	Estimates)
Dermal	LD50	36,667 mg/kg
Inhalative	LC50/4 h	50 mg/l
CAS: 7783	3-28-0 dian	nmonium hydrogenorthophosphate
Dermal	LD50	1,100 mg/kg (ATE)
Inhalative	LC50/4 h	1.5  mg/l (ATE)
CAS: 7664	1-41-7 amn	nonia, anhydrous
Oral	LD50	350 mg/kg (rat)

 Oral
 LD50
 350 mg/kg (rat)

 Inhalative
 LC50/4 h
 2,000 mg/l (rat)

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.

(Contd. on page 8)



Printing date: 19.10.2023 Version number 3 (replaces version 2) Revision: 19.10.2023

Trade name: ECOLYT SG 200

(Contd. of page 7)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment Not applicable.
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation





Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

Waste disposal key:

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Packaging which is uncleaned or soiled with product remains is to be treated like the product itself Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

### SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, IMDG, IATA Void

(Contd. on page 9)

Heimerle + Meule

Printing date: 19.10.2023 Version number 3 (replaces version 2) Revision: 19.10.2023

Trade name: ECOLYT SG 200

	(Contd. of p	page
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA		
· Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:		
· Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk according	g to IMO	
instruments	Not applicable.	
· Transport/Additional information:		
· IATA · Remarks:		
2.0	24h emergency contact -	
	(Dangerous goods emergency number)	
	+49 172 739 6970	
· UN "Model Regulation":	Void	

## **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

- · GADSL Global Automotive Declarable Substance List

  CAS: 7758-99-8 | Copper(II)sulphate-Pentahydrat | D/P(LR)
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- · Waterhazard class: .
- · Other regulations, limitations and prohibitive regulations -
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Reasons for revise

If necessary, this saftey data sheet can revised according to legal guidelines.

(Contd. on page 10)

Heimerle + Meule

Printing date: 19.10.2023 Version number 3 (replaces version 2) Revision: 19.10.2023

Trade name: ECOLYT SG 200

(Contd. of page 9)

Our current version for your reference is available on our website www.heimerle-meule.com

#### · Relevant phrases

- H221 Flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H400 Very toxic to aquatic life.

EUH031 Contact with acids liberates toxic gas.

#### Department issuing SDS:

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt Department BASU - Construction / Occupational Safety / Environment

sds@heimerle-meule.com

#### .

#### · Contact:

Herr Thomas Knuth

thomas.knuth@heimerle-meule.com

sds@heimerle-meule.com

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

AwSV: Ordinance on facilities for handling water-polluting substances (German regulation).

TRGS: Technical rules for hazardous substances (German regulation)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 2: Flammable gases – Category 2

Press. Gas (Comp.): Gases under pressure - Compressed gas

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 3: Acute toxicity - Category 3

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation — Category 2 STOT SE 3: Specific target organ toxicity (single exposure) — Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

#### \* Data compared to the previous version altered.