

Printing date: 21.12.2022 Version number 2 (replaces version 1) Revision: 21.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Make-up salt GP 205 S A
Ansatzsalz GP 205 S A

· Article number: 81024433

· 1.2 Relevant identified uses of the substance or mixture and uses advised against Not approved for private consumers.

· Application of the substance / the mixture

Electroplating auxiliary

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Heimerle + Meule GmbH Dennigstrasse 16 D-75179 Pforzheim

Telefon +49 (0) 7231 940-0 Telefax +49 (0) 7231 940-2199 www.heimerle-meule.com

Further information obtainable from:

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt Department BASU - Construction / Occupational Safety / Environment sds@heimerle-meule.com

IATA - 24h Emergency Contact - IATA - 24h Emergency Contact - (Dangerous goods emergency number) +49 172 739 6970

· 1.4 Emergency telephone number:

DEUTSCHLAND - GERMANY:

Vergiftungs-Informations-Zentrale Freiburg, ++49 761 19240 (24 h)

(Poisoning Information Center)

GREAT BRITAIN:

National Poisons Information Service +44 121 507 4123

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111 - In Scotland: NHS 24 - dial 111 IRELAND

+353 1 809 2166 (7 Days 8 am -10 pm)

Healthcare Professionals: +353 1 809 2566

ITALY:

Istituto Superiore di Sanità (ISS) +3906499906140

Centro Antiveleni

Bergamo: +39 800 883300 Firenze +39 055 794 7819 Milano: +39 055 794 7819 Roma +39 06 68593726

Roma +39 06 49978000 Roma +39 06 3954343

KROATIA - REPUBLIKA HRVATSKA:

(+385) 01 2348 342

ESTLAND - ESTONIA:

Tervisemeti Mürgistusteabekeskuse

National (24/7): 16662 (+372) 7943 794

(Contd. on page 2)



Printing date: 21.12.2022 Version number 2 (replaces version 1) Revision: 21.12.2022

Trade name: Make-up salt GP 205 S A Ansatzsalz GP 205 S A

(Contd. of page 1)

LETTLAND - LATVIA:

Valsts Toksikoloģijas centrs, Saindēšanās un zāļu informācijas centrs,

(24h) 112

(24h) +371 67042473

LITAUEN - LIETUVOS RESPUBLIKA:

Poison Information Bureau (24/7), Tel.: +8 5 236 20 52

Apsinuodijimų informacijos biuras

.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Muta. 2 H341 Suspected of causing genetic defects. Carc. 1A H350i May cause cancer by inhalation.

Repr. 1B H360FD May damage fertility. May damage the unborn child.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure. Route of

exposure: Inhalation.



Eye Dam. 1 H318 Causes serious eye damage.



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 3)

Heimerle + Meule

Printing date: 21.12.2022 Version number 2 (replaces version 1) Revision: 21.12.2022

Trade name: Make-up salt GP 205 S A Ansatzsalz GP 205 S A

(Contd. of page 2)

· Hazard pictograms



· Signal word Danger

Hazard-determining components of labelling:

tetrasodium ethylenediaminetetraacetate

boric acid

nickel sulphate

· Hazard statements

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.H341 Suspected of causing genetic defects.

H350i May cause cancer by inhalation.

H360FD May damage fertility. May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure. Route of exposure: Inhalation.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Restricted to professional users.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components / Information on ingredients:		
	boric acid; boric acid, crude natural, containing notmore than 85	
	per cent of H3BO3 calculated onthe dry weight; Boraric acid	
Index number: 005-007-00-2	powder, min 99.9 %	
	♦ Repr. 1B, H360FD	
Reg.nr.: 01-2119486683-25	Specific concentration limit: Repr. 1B; H360: $C \ge 5.5 \%$	
CAS: 64-02-8	tetrasodium ethylenediaminetetraacetate	10–25%
	♦ STOT RE 2, H373	
Index number: 607-428-00-2	Eye Dam. 1, H318	
RTECS: AH 5075000	♦ Acute Tox. 4, H302; Acute Tox. 4, H332	
KIECS. AII 50/5000	V	d on no

(Contd. on page 4)



Printing date: 21.12.2022 Version number 2 (replaces version 1) Revision: 21.12.2022

Trade name: Make-up salt GP 205 S A Ansatzsalz GP 205 S A

CAS: 7786-81-4
EINECS: 232-104-9
Index number: 028-009-00-5

Resp. Sens. 1, H334; Muta. 2, H341; Carc. 1A, H350i; Repr. 1B, H360D; STOT RE 1, H372
Aquatic Acute 1, H400; Aquatic Chronic 1, H410
Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317
Specific concentration limits: STOT RE 1; H372: $C \ge 1$ %
SKin Irrit. 2; H315: $C \ge 20$ %
Skin Sens. 1; H317: $C \ge 0.01$ %

·SVHC

CAS: 10043-35-3 boric acid

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

Involve doctor immediately after a accident or unwell

· After inhalation:

Take affected persons into fresh air and keep quiet.

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Drink plenty of water and provide fresh air. Call for a doctor immediately.

A person vomiting while laying on their back should be turned onto their side.

Rinse out mouth and then drink plenty of water.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

-GB



Printing date: 21.12.2022 Version number 2 (replaces version 1) Revision: 21.12.2022

Trade name: Make-up salt GP 205 S A Ansatzsalz GP 205 S A

(Contd. of page 4)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Only handle and refill product in closed systems.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Thorough dedusting.

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

he usual precautionary measures are to be adhered to when handling chemicals.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not dry clean dust covered objects and floors. Wash thoroughly with plenty of water.

- Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings.

Observe official regulations on storing packagings.

Prevent any seepage into the ground.

Information about storage in one common storage facility:

Store away from foodstuffs.

· Further information about storage conditions:

Keep container tightly sealed.

Store under lock and key and out of the reach of children.

- · Storage class: 6.1 D
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:		
CAS: 10043-35-3 boric acid		
AGW (Germany)	Long-term value: 0.5* mg/m³	
	2(I); *einatembar; AGS, Y, 10	

(Contd. on page 6)



Version number 2 (replaces version 1) Revision: 21.12.2022 Printing date: 21.12.2022

Trade name: Make-up salt GP 205 S A Ansatzsalz GP 205 S A

CAG. 7707 01 4	(Conta. of page 5)
CAS: 7786-81-4 nicke	et sutphate
WEL (Great Britain)	Long-term value: 0.1 mg/m³ as Ni; Sk; Carc; Sen
AGW (Germany)	Long-term value: 0.030E mg/m³ 8(II);AGS, Sh, Y, 10, 24, 31
,	Short-term value: 0.006 (A) mg/m³ Long-term value: 0.006 (A) mg/m³ 8, Konzentrationen beziehen sich auf Ni-Gehalt

Regulatory information

AGW (Germany): TRGS 900 WEL (Great Britain): EH40/2020

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

According to EC Directive 89/686/EEC

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire.

according EN 14387 according to EN 143

- · Recommended filter device for short term use: Filter P3
- · Hand protection



Protective gloves

according to EN 374

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

Sensibilisation by the components in the glove materials is possible.

Check the permeability prior to each anewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Prior to working with gloves the rubbing in with tanniferous skin-protecting agents for the avoidance of skin softening due to perspiration is recommended.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.65 mm

Chloroprene rubber, CR

Recommended thickness of the material: ≥ 0.65 mm

(Contd. on page 7)



Printing date: 21.12.2022 Version number 2 (replaces version 1) Revision: 21.12.2022

Trade name: Make-up salt GP 205 S A Ansatzsalz GP 205 S A

(Contd. of page 6)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 3).

Value for the permeation: Level ≤ 3

· Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

· Eye/face protection



Tightly sealed goggles

according to EN 166

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Solid · Colour: White

Odour: Product specific
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range Undetermined.
Flammability Not determined.

· Lower and upper explosion limit

Lower: Not determined.
 Upper: Not determined.
 Flash point: Not applicable.
 Decomposition temperature: Not determined.

 $\cdot pH \text{ at } 20^{\circ}C \text{ (68°F)}$ 6.7 (10%)

· Viscosity:

Kinematic viscosityDynamic:Not applicable.Not applicable.

·Solubility

· water: Soluble.

• Partition coefficient n-octanol/water (log value) Not determined. • Vapour pressure: Not applicable.

Density and/or relative density

Density:
Relative density
Bulk density:
Vapour density

Not determined.
950 kg/m³
Not applicable.

• 9.2 Other information 0.00 %

(Contd. on page 8)



Printing date: 21.12.2022 *Version number 2 (replaces version 1)* Revision: 21.12.2022

Trade name: Make-up salt GP 205 S A Ansatzsalz GP 205 S A

(Contd. of page 7)

· Appearance:

· Form: Powder

Important information on protection of health and

environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

· Solvent content:

· Solids content: 100 %

· Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void · Aerosols Void Void · Oxidising gases Void · Gases under pressure · Flammable liquids Void Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water

Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

· LD/LC50	· LD/LC50 values relevant for classification:	
ATE (Acua	te Toxicity	Estimates)
Oral	LD50	2,327 mg/kg
Inhalative	LC50/4 h	32.7 mg/l

0.40	10012	25 2	1 .	• 1
CAS:	10043-	·33-3	boric	асіа

CAS: 10043-35-3 boric acia		
Oral	LD50	2,660 mg/kg (rat)

(Contd. on page 9)



Printing date: 21.12.2022 Version number 2 (replaces version 1) Revision: 21.12.2022

Trade name: Make-up salt GP 205 S A Ansatzsalz GP 205 S A

- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- · Germ cell mutagenicity Suspected of causing genetic defects.
- · Carcinogenicity May cause cancer by inhalation.
- · Reproductive toxicity May damage fertility. May damage the unborn child.
- · STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure. Route of exposure: Inhalation.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment Not applicable.
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Danger to drinking water if even extremely small quantities leak into the ground.


Also poisonous for fish and plankton in water bodies.

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)



Printing date: 21.12.2022 Version number 2 (replaces version 1) Revision: 21.12.2022

Trade name: Make-up salt GP 205 S A Ansatzsalz GP 205 S A

(Contd. of page 9)

Contact manufacturer for recycling information.

· Waste disposal key:

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.


Packaging which is uncleaned or soiled with product remains is to be treated like the product itself Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish

• Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information
· 14.1 UN number or ID number

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3077
· 14.2 UN proper shipping name	
$\cdot ADR$	UN3077 ENVIRONMENTALLY HAZARDOUS
	SUBSTANCE, SOLID, N.O.S. (nickel sulphate)
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
	SOLID, N.O.S. (nickel sulphate), MARINE POLLUTANT
· IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
	SOLID, N.O.S. (nickel sulphate)

- · 14.3 Transport hazard class(es)
- · ADR, IMDG, IATA



· Class · Label	9 Miscellaneous dangerous substances and articles. 9
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: nickel sulphate
Marine pollutant:	No Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special marking (IATA):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
Hazard identification number (Kemler code):	90
· EMS Number:	F-A,S-F
· Stowage Category	A
· Stowage Code	SW23 When transported in BK3 bulk container, see

7.6.2.12 and 7.7.3.9.

(Contd. on page 11)



Printing date: 21.12.2022 Version number 2 (replaces version 1) Revision: 21.12.2022

Trade name: Make-up salt GP 205 S A Ansatzsalz GP 205 S A

	(Contd. of page 1
· 14.7 Maritime transport in bulk according instruments	g to IMO Not applicable.
· Transport/Additional information:	11
· ADR	
· Limited quantities (LQ)	5 kg
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g
· Transport category	3
· IMDG	
· Limited quantities (LQ)	5 kg
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 g
	Maximum net quantity per outer packaging: 1000 g
·IATA	
· Remarks:	
	24h emergency contact -
	(Dangerous goods emergency number)
	+49 172 739 6970
· UN "Model Regulation":	UN 3077 ENVIRONMENTALLY HAZARDOU SUBSTANCE, SOLID, N.O.S. (NICKEL SULPHATE), S III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

· GADSL - Global A	Automotive Declarable Substance List	
CAS: 10043-35-3	boric acid	D/P(LR)
CAS: 7786-81-4	nickel sulphate	D(FI)

- · Directive 2012/18/EU
- $\cdot \textit{Named dangerous substances-ANNEX I} \ \textit{None of the ingredients is listed}.$
- · Seveso category E2 Hazardous to the Aquatic Environment
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

Employment restrictions concerning juveniles must be observed.

(Contd. on page 12)



Printing date: 21.12.2022 Version number 2 (replaces version 1) Revision: 21.12.2022

Trade name: Make-up salt GP 205 S A Ansatzsalz GP 205 S A

(Contd. of page 11)

Employment restrictions concerning pregnant and lactating women must be observed. Employment restrictions concerning women of child-bearing age must be observed.

· Technical instructions (air):

Class	Share in %
II	2.5–7

- · Waterhazard class: .
- · Other regulations, limitations and prohibitive regulations -
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Reasons for revise

If necessary, this saftey data sheet can revised according to legal guidelines.

Our current version for your reference is available on our website www.heimerle-meule.com

· Relevant phrases

11202	II	. f 1 : f		1
H302	патт	иш и	swan	lowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H341 Suspected of causing genetic defects.

H350i May cause cancer by inhalation.

H360D May damage the unborn child.

H360FD May damage fertility. May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Department issuing SDS:

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt

Department BASU - Construction / Occupational Safety / Environment

sds@heimerle-meule.com

· Contact:

Herr Thomas Knuth

thomas.knuth@heimerle-meule.com

sds@heimerle-meule.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

AwSV: Ordinance on facilities for handling water-polluting substances (German regulation).

TRGS: Technical rules for hazardous substances (German regulation)

(Contd. on page 13)



Printing date: 21.12.2022 Version number 2 (replaces version 1) Revision: 21.12.2022

Trade name: Make-up salt GP 205 S A Ansatzsalz GP 205 S A

(Contd. of page 12)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 2: Germ cell mutagenicity – Category 2

Carc. 1A: Carcinogenicity – Category 1Ai

Repr. 1B: Reproductive toxicity - Category 1B

Repr. 1B: Reproductive toxicity – Category 1B

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* * Data compared to the previous version altered.

- GB