

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 26.07.2022

Version number 9

Revision: 26.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** Nickel replenishing salt NI
Nickelergänzungssalz NI

· **Article number:** 86900020

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
Not approved for private consumers.

· **Application of the substance / the mixture** Electroplating material

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Heimerle + Meule GmbH
Dennigstrasse 16
D-75179 Pforzheim

Telefon +49 (0) 7231 940-0
Telefax +49 (0) 7231 940-2199
www.heimerle-meule.com

· **Further information obtainable from:**

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt
Department BASU - Construction / Occupational Safety / Environment
sds@heimerle-meule.com

IATA - 24h Emergency Contact - IATA - 24h Emergency Contact -
(Dangerous goods emergency number)
+49 172 739 6970

· **1.4 Emergency telephone number:**

DEUTSCHLAND - GERMANY:

Vergiftungs-Informationen-Zentrale Freiburg, ++49 761 19240 (24 h)
(Poisoning Information Center)

GREAT BRITAIN:

National Poisons Information Service +44 121 507 4123

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111 - In Scotland: NHS 24 - dial 111

ITALY:

Istituto Superiore di Sanità +3906499906140

KROATIA - REPUBLIKA HRVATSKA:

(+385) 01 2348 342

ESTLAND - ESTONIA:

Tervisemeti Mürgistusteabekeskuse 16662, (+342) 7914 794

LETTLAND - LATVIA:

Latvijas Vides, ģeoloģijas un meteoroloģijas centrs (+371) 670 32600

LITAUEN - LIETUVOS RESPUBLIKA:

Apsinuodijimų informacijos biuras +370 (85) 2362052

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 26.07.2022

Version number 9

Revision: 26.07.2022

Trade name: Nickel replenishing salt N1
Nickelergänzungssalz N1

(Contd. of page 1)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



health hazard

Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Muta. 2	H341	Suspected of causing genetic defects.
Carc. 1A	H350i	May cause cancer by inhalation.
Repr. 1B	H360D	May damage the unborn child.
STOT RE 1	H372	Causes damage to the respiratory system and the male genitalia through prolonged or repeated exposure. Route of exposure: Inhalation.



environment

Aquatic Acute 1	H400	Very toxic to aquatic life.
Aquatic Chronic 1	H410	Very toxic to aquatic life with long lasting effects.



Acute Tox. 4	H302	Harmful if swallowed.
Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



GHS07



GHS08



GHS09

- Signal word *Danger*
- Hazard-determining components of labelling:
nickel sulphate
- Hazard statements
H302+H332 Harmful if swallowed or if inhaled.
H315 Causes skin irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 26.07.2022

Version number 9

Revision: 26.07.2022

Trade name: Nickel replenishing salt N1
Nickelergänzungssalz N1




(Contd. of page 2)

- H341 Suspected of causing genetic defects.
 H350i May cause cancer by inhalation.
 H360D May damage the unborn child.
 H372 Causes damage to the respiratory system and the male genitalia through prolonged or repeated exposure. Route of exposure: Inhalation.
 H410 Very toxic to aquatic life with long lasting effects.
- **Precautionary statements**
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**
 Restricted to professional users.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
 · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
 · **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components / Information on ingredients:**

CAS: 7786-81-4 EINECS: 232-104-9 Index number: 028-009-00-5	<i>nickel sulphate; nickel sulfate</i>  Resp. Sens. 1, H334; Muta. 2, H341; Carc. 1A, H350i; Repr. 1B, H360D; STOT RE 1, H372  Aquatic Acute 1, H400; Aquatic Chronic 1, H410  Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limits: STOT RE 1; H372: C ≥ 1 % STOT RE 2; H373: 0.1 % ≤ C < 1 % Skin Irrit. 2; H315: C ≥ 20 % Skin Sens. 1; H317: C ≥ 0.01 %	50–100%
---	--	---------

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
 Immediately remove any clothing soiled by the product.
 Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
 Personal protection for the First Aider.
 Take affected persons out of danger area and lay down.
 Involve doctor immediately after a accident or unwell
- **After inhalation:**
 Supply fresh air and to be sure call for a doctor.
 In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
 Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 26.07.2022

Version number 9

Revision: 26.07.2022

Trade name: Nickel replenishing salt N1
Nickelergänzungssalz N1

(Contd. of page 3)

*Immediately rinse with water.**If skin irritation continues, consult a doctor.*· **After eye contact:** *Rinse opened eye for several minutes under running water.*· **After swallowing:***Call a doctor immediately.**Drink plenty of water and provide fresh air. Call for a doctor immediately.**A person vomiting while laying on their back should be turned onto their side.**Rinse out mouth and then drink plenty of water.*· **4.2 Most important symptoms and effects, both acute and delayed** *No further relevant information available.*· **4.3 Indication of any immediate medical attention and special treatment needed***No further relevant information available.*

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**· **Suitable extinguishing agents:***CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.*· **For safety reasons unsuitable extinguishing agents:** *Water with full jet*· **5.2 Special hazards arising from the substance or mixture***Formation of toxic gases is possible during heating or in case of fire.*· **5.3 Advice for firefighters**· **Protective equipment:***Wear self-contained respiratory protective device.*· **Additional information***Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.*

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures***Mount respiratory protective device.**Wear protective equipment. Keep unprotected persons away.**Use respiratory protective device against the effects of fumes/dust/aerosol.**Only handle and refill product in closed systems.*· **6.2 Environmental precautions:***Taking up mechanically and collect in a suitable container**Do not allow product to reach sewage system or any water course.**Inform respective authorities in case of seepage into water course or sewage system.**Do not allow to enter sewers/ surface or ground water.*· **6.3 Methods and material for containment and cleaning up:***Dispose contaminated material as waste according to item 13.**Ensure adequate ventilation.*· **6.4 Reference to other sections***See Section 7 for information on safe handling.**See Section 8 for information on personal protection equipment.**See Section 13 for disposal information.*

GB

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 26.07.2022

Version number 9

Revision: 26.07.2022

Trade name: Nickel replenishing salt N1
Nickelergänzungssalz N1

(Contd. of page 4)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Provide suction extractors if dust is formed.

Extractor required at the object.

Thorough dedusting.

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

The usual precautionary measures are to be adhered to when handling chemicals.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not dry clean dust covered objects and floors. Wash thoroughly with plenty of water.

· **Information about fire - and explosion protection:** Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings .

Observe official regulations on storing packagings .

Prevent any seepage into the ground.

· Information about storage in one common storage facility:

Store away from foodstuffs.

· **Further information about storage conditions:** Keep container tightly sealed.

· **Storage class:** 6.1 D

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Additional information about design of technical facilities:** No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

CAS: 7786-81-4 nickel sulphate

WEL (Great Britain)	Long-term value: 0.1 mg/m ³ as Ni; Sk; Carc; Sen
AGW (Germany)	Long-term value: 0.030E mg/m ³ 8(II); AGS, Sh, Y, 10, 24, 31
TRGS 910 (Germany)	Short-term value: 0.006 (A) mg/m ³ Long-term value: 0.006 (A) mg/m ³ 8, Konzentrationen beziehen sich auf Ni-Gehalt

· Regulatory information

WEL (Great Britain): EH40/2020

AGW (Germany): TRGS 900

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 26.07.2022

Version number 9

Revision: 26.07.2022

Trade name: Nickel replenishing salt N1
Nickelergänzungssalz N1

(Contd. of page 5)

Avoid contact with the skin.

Avoid contact with the eyes and skin.

According to EC Directive 89/686/EEC

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire.

according to EN 14387

according to EN 143

· **Recommended filter device for short term use: Filter P3**

· **Protection of hands:**



Protective gloves

according to EN 374

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

Sensibilisation by the components in the glove materials is possible.

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Prior to working with gloves the rubbing in with tanniferous skin-protecting agents for the avoidance of skin softening due to perspiration is recommended.

· **Material of gloves**

Chloroprene rubber, CR

Recommended thickness of the material: ≥ 0.65 mm

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.65 mm

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 3).

Value for the permeation: Level ≤ 3

· **Not suitable are gloves made of the following materials:**

Leather gloves

Strong material gloves

· **Eye protection:**



Tightly sealed goggles

according to EN 166

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 26.07.2022

Version number 9

Revision: 26.07.2022

Trade name: Nickel replenishing salt N1
Nickelergänzungssalz N1

(Contd. of page 6)

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

· **Form:** Powder

· **Colour:** Green

· **Odour:** Odourless

· **Odour threshold:** Not determined.

· **pH-value at 20°C (68°F):** 6 (1%) (H₂O)

· Change in condition

· **Melting point/freezing point:** Undetermined.

· **Initial boiling point and boiling range:** Undetermined.

· **Flash point:** Not applicable.

· **Flammability (solid, gas):** Not determined.

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product does not present an explosion hazard.

· Explosion limits:

· **Lower:** Not determined.

· **Upper:** Not determined.

· **Vapour pressure:** Not applicable.

· **Density:** Not determined.

· **Relative density at 20°C (68°F)** 2.07 g/cm³ (17.27 lbs/gal)

· **Vapour density** Not applicable.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with water at 20°C (68°F):**

625 g/l

· **Partition coefficient: n-octanol/water:** Not determined.

· Viscosity:

· **Dynamic:** Not applicable.

· **Kinematic:** Not applicable.

· Solvent content:

· **Solids content:** 100.0 %

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:** To avoid thermal decomposition do not overheat.

· **10.3 Possibility of hazardous reactions** Reacts with acids, alkalis and oxidising agents.

· **10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 26.07.2022

Version number 9

Revision: 26.07.2022

Trade name: Nickel replenishing salt N1
Nickelergänzungssalz N1

(Contd. of page 7)

- **10.5 Incompatible materials: Acids**
- **10.6 Hazardous decomposition products: No dangerous decomposition products known.**

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

Harmful if swallowed or if inhaled.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	556 mg/kg
Inhalative	LC50/4 h	1.67 mg/l

CAS: 7786-81-4 nickel sulphate

Oral	LD50	500 mg/kg (ATE)
Inhalative	LC50/4 h	1.5 mg/l (ATE)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity**
Suspected of causing genetic defects.
- **Carcinogenicity**
May cause cancer by inhalation.
- **Reproductive toxicity**
May damage the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
Causes damage to the respiratory system and the male genitalia through prolonged or repeated exposure.
Route of exposure: Inhalation.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

· Ecotoxicological effects:

· **Remark:** Very toxic for fish

· Additional ecological information:

· General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 26.07.2022

Version number 9

Revision: 26.07.2022


Trade name: Nickel replenishing salt N1
Nickelergänzungssalz N1

(Contd. of page 8)

- *Very toxic for aquatic organisms*
- **12.5 Results of PBT and vPvB assessment** Not applicable.
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**




Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

- **Waste disposal key:**
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.
- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Packaging which is uncleaned or soiled with product remains is to be treated like the product itself
Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- | | |
|---|---|
| · 14.1 UN-Number
· ADR, IMDG, IATA | UN3077 |
| · 14.2 UN proper shipping name
· ADR
· IMDG, IATA | UN3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (nickel sulphate)
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (nickel sulphate) |
| · 14.3 Transport hazard class(es)
· ADR, IATA | |
|  | |
| · Class | 9 Miscellaneous dangerous substances and articles. |

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 26.07.2022

Version number 9

Revision: 26.07.2022

Trade name: Nickel replenishing salt N1
Nickelergänzungssalz N1

(Contd. of page 9)

· Label	9

· IMDG	
	
· Class	9 Miscellaneous dangerous substances and articles.
· Label	9

· 14.4 Packing group	III
· ADR, IMDG, IATA	III

· 14.5 Environmental hazards:	
· Marine pollutant:	No
· Special marking (ADR):	Symbol (fish and tree)
· Special marking (IATA):	Symbol (fish and tree)

· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
· Hazard identification number (Kemler code):	90
· EMS Number:	F-A,S-F
· Stowage Category	A
· Stowage Code	SW23 When transported in BK3 bulk container, see 7.6.2.12 and 7.7.3.9.

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.

· Transport/Additional information:	

· ADR	
· Limited quantities (LQ)	5 kg
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g
· Transport category	3

· IMDG	
· Limited quantities (LQ)	5 kg
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g

· IATA	
· Remarks:	24h emergency contact - (Dangerous goods emergency number) +49 172 739 6970

· UN "Model Regulation":	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (NICKEL SULPHATE), 9, III

GB

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 26.07.2022

Version number 9

Revision: 26.07.2022

Trade name: Nickel replenishing salt N1
Nickelergänzungssalz N1

(Contd. of page 10)

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

· **GADSL - Global Automotive Declarable Substance List**

All substances have the value D(FI).

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category E1** Hazardous to the Aquatic Environment

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials, Annex II:**
Carcinogenic hazardous material group III (dangerous).

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

Employment restrictions concerning women of child-bearing age must be observed.

· **Technical instructions (air):**

Class	Share in %
II	90.0

· **Waterhazard class:** .

· **Other regulations, limitations and prohibitive regulations -**

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Reasons for revise**

If necessary, this safety data sheet can be revised according to legal guidelines.

Our current version for your reference is available on our website
www.heimerle-meule.com

· **Relevant phrases**

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 26.07.2022

Version number 9

Revision: 26.07.2022

Trade name: Nickel replenishing salt N1
Nickelergänzungssalz N1

(Contd. of page 11)

- H341 Suspected of causing genetic defects.
 H350i May cause cancer by inhalation.
 H360D May damage the unborn child.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.

· **Department issuing SDS:**

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt
 Department BASU - Construction / Occupational Safety / Environment

sds@heimerle-meule.com

· **Contact:**

Herr Thomas Knuth
 thomas.knuth@heimerle-meule.com
 sds@heimerle-meule.com

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
 ICAO: International Civil Aviation Organisation
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
 AwSV: Ordinance on facilities for handling water-polluting substances (German regulation).
 TRGS: Technical rules for hazardous substances (German regulation)
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Resp. Sens. 1: Respiratory sensitisation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 Muta. 2: Germ cell mutagenicity – Category 2
 Carc. 1A: Carcinogenicity – Category 1Ai
 Repr. 1B: Reproductive toxicity – Category 1B
 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

· *** Data compared to the previous version altered.**