

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 04.03.2019

Version number 8

Revision: _____ 04.03.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** Nickel Replenishing salt N2

Nickelergänzungssalz N2

· **Article number:** 86900189

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
Not approved for private consumers.

· **Application of the substance / the mixture** Electroplating material

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Heimerle + Meule GmbH
Dennigstrasse 16
D-75179 Pforzheim

Telefon +49 (0) 7231 940-0
Telefax +49 (0) 7231 940-2199

www.heimerle-meule.com

· **Further information obtainable from:**

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt
sds@heimerle-meule.com

IATA - 24h Emergency Contact -
(Gefahrgut-Notrufnummer)
+49 172 739 6970

· **1.4 Emergency telephone number:**

Vergiftungs-Informationen-Zentrale Freiburg, ++49 761 19240 (24 h)

·
·

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



GHS06 skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 04.03.2019

Version number 8

Revision: _____ 04.03.2019

Trade name: Nickel Replenishing salt N2
Nickelergänzungssalz N2

(Contd. of page 1)

Muta. 2 H341 Suspected of causing genetic defects.
Carc. 1A H350i May cause cancer by inhalation.
Repr. 1B H360D May damage the unborn child.
STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.
Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS06



GHS08



GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**

nickel dichloride

· **Hazard statements**

H301+H331 Toxic if swallowed or if inhaled.
H315 Causes skin irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H350i May cause cancer by inhalation.
H360D May damage the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H410 Very toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P321 Specific treatment (see on this label).
P330 Rinse mouth.
P362+P364 Take off contaminated clothing and wash it before reuse.
P405 Store locked up.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 04.03.2019

Version number 8

Revision: _____ 04.03.2019

Trade name: Nickel Replenishing salt N2
Nickelergänzungssalz N2

(Contd. of page 2)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

Restricted to professional users.

· **Labelling of packages where the contents do not exceed 125 ml**

· **Hazard pictograms**



GHS06



GHS08



GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**

nickel dichloride

· **Hazard statements**

H301+H331 Toxic if swallowed or if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H350i May cause cancer by inhalation.

H360D May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P272 Contaminated work clothing should not be allowed out of the workplace.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P330 Rinse mouth.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.





· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components / Information on ingredients:**

CAS: 7718-54-9	nickel dichloride	50-100%
EINECS: 231-743-0	 Acute Tox. 3, H301; Acute Tox. 3, H331	
Index number: 028-011-00-6	 Resp. Sens. 1, H334; Muta. 2, H341; Carc. 1A, H350i; Repr. 1B, H360D; STOT RE 1, H372	
	 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	 Skin Irrit. 2, H315; Skin Sens. 1, H317	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 04.03.2019

Version number 8

Revision: _____ 04.03.2019

Trade name: Nickel Replenishing salt N2
Nickelergänzungssalz N2

(Contd. of page 3)

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Remove breathing equipment only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

Involve doctor immediately after a accident or unwell

· **After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Call a doctor immediately.

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

A person vomiting while laying on their back should be turned onto their side.

Rinse out mouth and then drink plenty of water.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **5.3 Advice for firefighters**

· **Protective equipment:**



Wear self-contained respiratory protective device.

· **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 04.03.2019

Version number 8

Revision: _____ 04.03.2019

Trade name: Nickel Replenishing salt N2
Nickelergänzungssalz N2

(Contd. of page 4)

Only handle and refill product in closed systems.

· **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Thorough dedusting.

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

he usual precautionary measures are to be adhered to when handling chemicals.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not dry clean dust covered objects and floors. Wash thoroughly with plenty of water.

· **Information about fire - and explosion protection:** Keep respiratory protective device available.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings .

Observe official regulations on storing packagings .

Prevent any seepage into the ground.

· **Information about storage in one common storage facility:**

Do not store together with acids.

Store away from foodstuffs.

· **Further information about storage conditions:**

Store in dry conditions.

Keep container tightly sealed.



Store under lock and key and with access restricted to technical experts or their assistants only.

Store under lock and key and out of the reach of children.

· **Storage class:** 6.1 D

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 04.03.2019

Version number 8

Revision: _____ 04.03.2019

Trade name: Nickel Replenishing salt N2
Nickelergänzungssalz N2

(Contd. of page 5)

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 7718-54-9 nickel dichloride

WEL (Great Britain)	Long-term value: 0.1 mg/m ³ as Ni; Sk; Carc; Sen
AGW (Germany)	Long-term value: 0.030E mg/m ³ 8(II); AGS, Sh, Y, 10, 24, 31
TRGS 910 (Germany)	Short-term value: 0.006 (A) mg/m ³ Long-term value: 0.006 (A) mg/m ³ 8, Konzentrationen beziehen sich auf Ni-Gehalt

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

According to EC Directive 89/686/EEC

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire.

according EN 14387

according to EN 143

· **Recommended filter device for short term use: Filter P3**

· **Protection of hands:**



Protective gloves

according to EN 374

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

Sensibilisation by the components in the glove materials is possible.

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Prior to working with gloves the rubbing in with tanniferous skin-protecting agents for the avoidance of skin softening due to perspiration is recommended.

· **Material of gloves**

Chloroprene rubber, CR

Recommended thickness of the material: ≥ 0.65 mm

Nitrile rubber, NBR

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 04.03.2019

Version number 8

Revision: _____ 04.03.2019

Trade name: Nickel Replenishing salt N2
Nickelergänzungssalz N2

(Contd. of page 6)

Recommended thickness of the material: ≥ 0.65 mm

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 3).

Value for the permeation: Level ≤ 3

· **Not suitable are gloves made of the following materials:**

Leather gloves

Strong material gloves

· **Eye protection:**



Tightly sealed goggles

according to EN 166

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Powder

Colour: Dark yellow

· **Odour:** Odourless

· **Odour threshold:** Not determined.

· **pH-value (50 g/l) at 20°C (68°F):** 6.1

· **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 973°C (1,783.4°F)

· **Flash point:** Not applicable.

· **Flammability (solid, gas):** Not determined.

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

· **Vapour pressure:** Not applicable.

· **Density at 20°C (68°F):** 3.55 g/cm³ (29.62 lbs/gal)

· **Relative density** Not determined.

· **Vapour density** Not applicable.

· **Evaporation rate** Not applicable.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 04.03.2019

Version number 8

Revision: _____ 04.03.2019

Trade name: Nickel Replenishing salt N2
Nickelergänzungssalz N2

(Contd. of page 7)

- | | |
|---|--|
| · Solubility in / Miscibility with water at 20°C (68°F): | 2540 g/l (H ₂ O) |
| · Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: | |
| Dynamic: | Not applicable. |
| Kinematic: | Not applicable. |
| · Solvent content: | |
| Solids content: | 100.0 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with acids, alkalis and oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** no information available

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
Toxic if swallowed or if inhaled.

- **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	111 mg/kg
Inhalative	LC50/4 h	0.56 mg/l

CAS: 7718-54-9 nickel dichloride

Oral	LD50	100 mg/kg (ATE)
Inhalative	LC50/4 h	0.5 mg/l (ATE)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity**
Suspected of causing genetic defects.
- **Carcinogenicity**
May cause cancer by inhalation.
- **Reproductive toxicity**
May damage the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 04.03.2019

Version number 8

Revision: _____ 04.03.2019

Trade name: Nickel Replenishing salt N2
Nickelergänzungssalz N2

(Contd. of page 8)


- **STOT-repeated exposure**
Causes damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Very toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment** Not applicable.
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

- **Waste disposal key:**
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.
- **European waste catalogue**
There are no uniform EC regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding laws and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste

11 00 00	WASTES FROM CHEMICAL SURFACE TREATMENT AND COATING OF METALS AND OTHER MATERIALS; NON-FERROUS HYDRO-METALLURGY
11 01 00	wastes from chemical surface treatment and coating of metals and other materials (for example galvanic processes, zinc coating processes, pickling processes, etching, phosphating, alkaline degreasing, anodising)
11 01 98*	other wastes containing hazardous substances
HP 4	Irritant - skin irritation and eye damage
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 04.03.2019

Version number 8

Revision: _____ 04.03.2019

Trade name: Nickel Replenishing salt N2
Nickelergänzungssalz N2

(Contd. of page 9)

HP 6	Acute Toxicity
HP 7	Carcinogenic
HP 10	Toxic for reproduction
HP 11	Mutagenic
HP 13	Sensitising
HP 14	Ecotoxic

- **Uncleaned packaging:**

- **Recommendation:**

Packaging which is uncleaned or soiled with product remains is to be treated like the product itself
Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish
Disposal must be made according to official regulations.

- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- **14.1 UN-Number**

- **ADR, IMDG, IATA**

UN3288

- **14.2 UN proper shipping name**

- **ADR**

UN3288 TOXIC SOLID, INORGANIC, N.O.S. (nickel dichloride), ENVIRONMENTALLY HAZARDOUS
TOXIC SOLID, INORGANIC, N.O.S. (nickel dichloride)

- **IMDG, IATA**

- **14.3 Transport hazard class(es)**

- **ADR**



- **Class**

6.1 Toxic substances.

- **Label**

6.1

- **IMDG, IATA**



- **Class**

6.1 Toxic substances.

- **Label**

6.1

- **14.4 Packing group**

- **ADR, IMDG, IATA**

III

- **14.5 Environmental hazards:**

- **Marine pollutant:**

No

- **Special marking (ADR):**

Symbol (fish and tree)

- **14.6 Special precautions for user**

Warning: Toxic substances.

- **Danger code (Kemler):**

60

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 04.03.2019

Version number 8

Revision: _____ 04.03.2019

Trade name: Nickel Replenishing salt N2
Nickelergänzungssalz N2

(Contd. of page 10)

· EMS Number:	F-A,S-A
· Stowage Category	A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	

· ADR	
· Limited quantities (LQ)	5 kg
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g
· Transport category	2
· Tunnel restriction code	E

· IMDG	
· Limited quantities (LQ)	5 kg
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g

· IATA	
· Remarks:	24h Emergency Contact - (Gefahrgut-Notrufnummer) +49 172 739 6970
· UN "Model Regulation":	UN 3288 TOXIC SOLID, INORGANIC, N.O.S. (NICKEL DICHLORIDE), 6.1, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
H2 ACUTE TOXIC
E1 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 27, 28, 30
- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials, Annex II:**
Carcinogenic hazardous material group III (dangerous).

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 04.03.2019

Version number 8

Revision: _____ 04.03.2019

Trade name: Nickel Replenishing salt N2
Nickelergänzungssalz N2

(Contd. of page 11)

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
Exceptions can be made by the authorities in certain cases.
Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.
Employment restrictions concerning women of child-bearing age must be observed.

· **Technical instructions (air):**

Class	Share in %
II	90.0

- **Waterhazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.
- **Other regulations, limitations and prohibitive regulations**
-
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Reasons for revise**

If necessary, this safety data sheet can revised according to legal guidelines.

Our current version for your reference is available on our website
www.heimerle-meule.com

- **Date from last issue :** 11.05.2017

· **Relevant phrases**

H301 Toxic if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H331 Toxic if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H341 Suspected of causing genetic defects.
H350i May cause cancer by inhalation.
H360D May damage the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

· **Department issuing SDS:**

Department BASU - Bau/Arbeitssicherheit/Umwelt

sds@heimerle-meule.com

· **Contact:**

Herr Thomas Knuth
Knuth@heimerle-meule.com
sds@heimerle-meule.com

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 04.03.2019

Version number 8

Revision: _____ 04.03.2019

Trade name: Nickel Replenishing salt N2
Nickelergänzungssalz N2

(Contd. of page 12)

*ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)**ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**GHS: Globally Harmonised System of Classification and Labelling of Chemicals**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**Acute Tox. 3: Acute toxicity – Category 3**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Resp. Sens. 1: Respiratory sensitisation – Category 1**Skin Sens. 1: Skin sensitisation – Category 1**Muta. 2: Germ cell mutagenicity – Category 2**Carc. 1A: Carcinogenicity – Category 1A**Repr. 1B: Reproductive toxicity – Category 1B**STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*

· *** Data compared to the previous version altered.**

GB