

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 15.10.2020

Version number 16

Revision: _____ 15.10.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:**

Silver conducting lacquer, 45,0 % Ag/kg

Silberleitlack, 45,0 % Ag/kg

· **Article number:** 86900559

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
Not approved for private consumers.

· **Application of the substance / the mixture** Masking material

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Heimerle + Meule GmbH
Dennigstrasse 16
D-75179 Pforzheim

Telefon +49 (0) 7231 940-0
Telefax +49 (0) 7231 940-2199
www.heimerle-meule.com

· **Further information obtainable from:**

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt
Department BASU - Construction / Occupational Safety / Environment
sds@heimerle-meule.com

IATA - 24h Emergency Contact - IATA - 24h Emergency Contact -
(Dangerous goods emergency number)
+49 172 739 6970

· **1.4 Emergency telephone number:**

DEUTSCHLAND - GERMANY:

Vergiftungs-Informations-Zentrale Freiburg, ++49 761 19240 (24 h)
(Poisoning Information Center)

GREAT BRITAIN:

National Poisons Information Service +44 121 507 4123
Members of the public seeking specific information on poisons should contact:
In England and Wales: NHS 111 - dial 111 - In Scotland: NHS 24 - dial 111

ITALY:

Istituto Superiore di Sanità +3906499906140

KROATIA - REPUBLIKA HRVATSKA:

(+385) 01 2348 342

ESTLAND - ESTONIA:

Tervisemeti Mürgistusteabekeskuse 16662, (+342) 7914 794

LETTLAND - LATVIA:

Latvijas Vides, ģeoloģijas un meteoroloģijas centrs (+371) 670 32600

LITAUEN - LIETUVOS RESPUBLIKA:

Apsinuodijimų informacijos biuras +370 (85) 2362052

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 15.10.2020

Version number 16

Revision: _____ 15.10.2020

Trade name: Silver conducting lacquer, 45,0 % Ag/kg
Silberleitlack, 45,0 % Ag/kg

(Contd. of page 1)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.
Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS02



GHS07



GHS09

- Signal word *Danger*
- Hazard-determining components of labelling:
1-ethoxypropan-2-ol
acetone
ethyl acetate
- Hazard statements
H225 Highly flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H410 Very toxic to aquatic life with long lasting effects.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P273 Avoid release to the environment.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P405 Store locked up.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 15.10.2020

Version number 16

Revision: _____ 15.10.2020

Trade name: Silver conducting lacquer, 45,0 % Ag/kg
Silberleitlack, 45,0 % Ag/kg

(Contd. of page 2)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Labelling of packages where the contents do not exceed 125 ml
- Hazard pictograms



GHS02

GHS07

GHS09

- Signal word *Danger*
- Hazard-determining components of labelling:
1-ethoxypropan-2-ol
acetone
ethyl acetate
- Hazard statements *Void*
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Chemical characterisation: *Mixtures*
- Description: *Mixture of substances listed below with nonhazardous additions.*

· **Dangerous components / Information on ingredients:**

CAS: 7440-22-4 EINECS: 231-131-3	silver; silver < 1µm particle size; Silver (Powder <0.0001µm); Nano silver as per EU recommended definition; Silver (Powder <1µm) ----- ☠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	45%
CAS: 1569-02-4 EINECS: 216-374-5 Index number: 603-177-00-8	1-ethoxypropan-2-ol; 2PG1EE; 1-ethoxy-2-propanol; propylene glycol monoethyl ether ----- ☠ Flam. Liq. 3, H226 ☠ STOT SE 3, H336	20-<25%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 RTECS: KQ 6300000 Reg.nr.: 01-2119457610-43	ethanol; ethyl alcohol; Alcohol; Ethyl hydroxide; Methyl carbinol ----- ☠ Flam. Liq. 2, H225 ☠ Eye Irrit. 2, H319	10-<20%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 RTECS: AL 3150000 Reg.nr.: 01-2119471330-49	acetone; propan-2-one; propanone; 2-Oxopropane; 2-Propanone; beta-Ketopropane; Dimethyl ketone; Pyroacetic ether ----- ☠ Flam. Liq. 2, H225 ☠ Eye Irrit. 2, H319; STOT SE 3, H336	3-<10%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 RTECS: AH 5425000 Reg.nr.: 01-2119475103-46	ethyl acetate; Acetic acid, ethyl ester; Acetic ether; Ethyl ethanoate; Vinegar naphtha ----- ☠ Flam. Liq. 2, H225 ☠ Eye Irrit. 2, H319; STOT SE 3, H336	1-<3%

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 15.10.2020

Version number 16

Revision: _____ 15.10.2020

Trade name: Silver conducting lacquer, 45,0 % Ag/kg
Silberleitlack, 45,0 % Ag/kg

(Contd. of page 3)

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Do not leave affected persons unattended.

Immediately remove any clothing soiled by the product.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

Involve doctor immediately after an accident or unwell

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

A person vomiting while laying on their back should be turned onto their side.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** Can form explosive gas-air mixtures.

· **5.3 Advice for firefighters**

· **Protective equipment:**



Wear self-contained respiratory protective device.

Wear fully protective suit.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Only handle and refill product in closed systems.

· **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 15.10.2020

Version number 16

Revision: _____ 15.10.2020

Trade name: Silver conducting lacquer, 45,0 % Ag/kg
Silberleitlack, 45,0 % Ag/kg

(Contd. of page 4)

- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
Ignition source distance
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep receptacles tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
The usual precautionary measures are to be adhered to when handling chemicals.
Prevent formation of aerosols.
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
Do not dry clean dust covered objects and floors. Wash thoroughly with plenty of water.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store only in the original receptacle.
Store in a cool location.
Observe official regulations on storing packagings .
Observe official regulations on storing packagings .
Prevent any seepage into the ground.
- **Information about storage in one common storage facility:**
Do not store together with materials which also support fire
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Store under lock and key and out of the reach of children.
- **Storage class: 3**
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 1569-02-4 1-ethoxypropan-2-ol

AGW (Germany)

Long-term value: 86 mg/m³, 20 ppm
2(II);DFG, H, Y, 14

(Contd. on page 6)

-GB-

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 15.10.2020

Version number 16

Revision: _____ 15.10.2020

Trade name: Silver conducting lacquer, 45,0 % Ag/kg
Silberleitlack, 45,0 % Ag/kg

(Contd. of page 5)

CAS: 64-17-5 ethanol

WEL (Great Britain)	Long-term value: 1920 mg/m ³ , 1000 ppm
AGW (Germany)	Long-term value: 380 mg/m ³ , 200 ppm 4(II);DFG, Y

CAS: 67-64-1 acetone

WEL (Great Britain)	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
IOELV (European Union)	Long-term value: 1210 mg/m ³ , 500 ppm
AGW (Germany)	Long-term value: 1200 mg/m ³ , 500 ppm 2(I);AGS, DFG, EU, Y

CAS: 141-78-6 ethyl acetate

WEL (Great Britain)	Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm
IOELV (European Union)	Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm
AGW (Germany)	Long-term value: 730 mg/m ³ , 200 ppm 2(I);DFG, EU, Y

· **Regulatory information**

AGW (Germany): TRGS 900
WEL (Great Britain): EH40/2020
IOELV (European Union): (EU) 2019/1831

· **Ingredients with biological limit values:****CAS: 67-64-1 acetone**

BGW (Germany)	80 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Aceton
---------------	---

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.
Apply solvent resistant skin cream before starting work.
The usual precautionary measures are to be adhered to when handling chemicals.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
According to EC Directive 89/686/EEC

· **Respiratory protection:**

Not necessary if room is well-ventilated.
Use suitable respiratory protective device only when aerosol or mist is formed.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire.

according to EN 14387

according to EN 143

· **Recommended filter device for short term use:** Combination filter A-P2· **Protection of hands:**

Solvent resistant gloves

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 15.10.2020

Version number 16

Revision: _____ 15.10.2020

Trade name: Silver conducting lacquer, 45,0 % Ag/kg
Silberleitlack, 45,0 % Ag/kg

(Contd. of page 6)

Check protective gloves prior to each use for their proper condition.



Protective gloves

according to EN 374

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

Sensibilisation by the components in the glove materials is possible.

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Prior to working with gloves the rubbing in with tanniferous skin-protecting agents for the avoidance of skin softening due to perspiration is recommended.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 120 - 240 minutes (Permeation according to EN 16523-1:2015: Level 4).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 3).

· **Not suitable are gloves made of the following materials:**

Leather gloves

Strong material gloves

· **Eye protection:**



Tightly sealed goggles

according to EN 166

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Fluid

Colour:

Silver-coloured

· **Odour:**

Acetone-like

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 15.10.2020

Version number 16

Revision: _____ 15.10.2020

Trade name: Silver conducting lacquer, 45,0 % Ag/kg
Silberleitlack, 45,0 % Ag/kg

(Contd. of page 7)

· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.
· Flash point:	< 23°C (< 73.4°F)
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.3 Vol %
Upper:	19 Vol %
· Vapour pressure:	Not determined.
· Density at 20°C (68°F):	1.45 g/cm ³ (12.1 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Partly soluble.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20°C (68°F):	473 mm ² /s
· Solvent content:	
Organic solvents:	38.3–55.3 %
Solids content:	45.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
When warming/heating exist explosion-fire risk
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with acids, alkalis and oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 15.10.2020

Version number 16

Revision: _____ 15.10.2020

Trade name: Silver conducting lacquer, 45,0 % Ag/kg
Silberleitlack, 45,0 % Ag/kg

(Contd. of page 8)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

CAS: 1569-02-4 1-ethoxypropan-2-ol

Oral	LD50	4,900 mg/kg (rat)
Dermal	LD50	9,500 mg/kg (rab)

CAS: 64-17-5 ethanol

Oral	LD50	7,060 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/l (rat)

CAS: 67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rbt)

CAS: 141-78-6 ethyl acetate

Oral	LD50	4,935 mg/kg (rbt)
Inhalative	LC50/4 h	1,600 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

CAS: 7440-22-4 silver

(Chronische) aquatische Toxizität	0.00012 mg/l (Fisch)
	0.0008 mg/l (wirbellose Wasserlebewesen)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Very toxic for fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Very toxic for aquatic organisms

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 15.10.2020

Version number 16

Revision: _____ 15.10.2020


Trade name: Silver conducting lacquer, 45,0 % Ag/kg
Silberleitlack, 45,0 % Ag/kg

(Contd. of page 9)

- **12.5 Results of PBT and vPvB assessment** Not applicable.
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

- **Waste disposal key:**
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.
- **European waste catalogue**
There are no uniform EC regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding laws and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste

11 00 00	WASTES FROM CHEMICAL SURFACE TREATMENT AND COATING OF METALS AND OTHER MATERIALS; NON-FERROUS HYDRO-METALLURGY
11 01 00	wastes from chemical surface treatment and coating of metals and other materials (for example galvanic processes, zinc coating processes, pickling processes, etching, phosphating, alkaline degreasing, anodising)
11 01 98*	other wastes containing hazardous substances
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP14	Ecotoxic

- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Packaging which is uncleaned or soiled with product remains is to be treated like the product itself
Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish
- **Recommended cleansing agents:**
Alcohol
Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1993

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 15.10.2020


Version number 16

Revision: _____ 15.10.2020

Trade name: Silver conducting lacquer, 45,0 % Ag/kg
Silberleitlack, 45,0 % Ag/kg

(Contd. of page 10)

· **14.2 UN proper shipping name**
· **ADR** *UN1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL), ACETONE), ENVIRONMENTALLY HAZARDOUS, special provision 640C*
· **IMDG** *FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL), ACETONE)*
· **IATA** *FLAMMABLE LIQUID, N.O.S. (ETHANOL, ACETONE)*

· **14.3 Transport hazard class(es)**· **ADR**

· **Class** *3 Flammable liquids.*
· **Label** *3*

· **IMDG, IATA**

· **Class** *3 Flammable liquids.*
· **Label** *3*

· **14.4 Packing group**· **ADR, IMDG, IATA** *II*· **14.5 Environmental hazards:**

· **Marine pollutant:** *Yes*
· **Special marking (ADR):** *Symbol (fish and tree)*

· **14.6 Special precautions for user** *Warning: Flammable liquids.*· **Hazard identification number (Kemler code):** *33*· **EMS Number:** *F-E,S-E*· **Stowage Category** *B*

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** *Not applicable.*

· **Transport/Additional information:**· **ADR**

· **Limited quantities (LQ)** *1L*
· **Excepted quantities (EQ)** *Code: E2*
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· **Transport category** *2*· **Tunnel restriction code** *D/E*· **IMDG**· **Limited quantities (LQ)** *1L*

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 15.10.2020

Version number 16

Revision: _____ 15.10.2020

Trade name: Silver conducting lacquer, 45,0 % Ag/kg
Silberleitlack, 45,0 % Ag/kg

(Contd. of page 11)

· **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· **IATA**
· **Remarks:**
24h emergency contact -
(Dangerous goods emergency number)

+49 172 739 6970

· **UN "Model Regulation":** UN 1993 FLAMMABLE LIQUID, N.O.S., SPECIAL PROVISION 640C (ETHANOL (ETHYL ALCOHOL), ACETONE), 3, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

· **TSCA (Toxic Substances Control Act)**

CAS: 7440-22-4	silver
CAS: 64-17-5	ethanol
CAS: 9004-70-0	nitrocellulose solutions, with not more than 12.6% nitrogen, by dry mass, and not more than 55% nitrocellulose
CAS: 67-64-1	acetone
CAS: 141-78-6	ethyl acetate

· **GADSL - Global Automotive Declarable Substance List**

CAS: 7440-22-4	silver	D(LR)
CAS: 9004-70-0	nitrocellulose solutions, with not more than 12.6% nitrogen, by dry mass, and not more than 55% nitrocellulose	D(FI)

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 15.10.2020

Version number 16

Revision: _____ 15.10.2020

Trade name: Silver conducting lacquer, 45,0 % Ag/kg
Silberleitlack, 45,0 % Ag/kg

(Contd. of page 12)

· **National regulations:**· **Technical instructions (air):**

Class	Share in %
NK	50

· **Waterhazard class:** .· **Other regulations, limitations and prohibitive regulations -**· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Reasons for revise**

If necessary, this safety data sheet can be revised according to legal guidelines.

Our current version for your reference is available on our website
www.heimerle-meule.com

· **Date from last issue :** 01.04.2020· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· **Department issuing SDS:**

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt

Department BASU - Construction / Occupational Safety / Environment

sds@heimerle-meule.com· **Contact:**

Herr Thomas Knuth

Knuth@heimerle-meule.comsds@heimerle-meule.com· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

AwSV: Ordinance on facilities for handling water-polluting substances (German regulation).

TRGS: Technical rules for hazardous substances (German regulation)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 14)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 15.10.2020

Version number 16

Revision: _____ 15.10.2020

Trade name: Silver conducting lacquer, 45,0 % Ag/kg
Silberleitlack, 45,0 % Ag/kg

(Contd. of page 13)

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

· *** Data compared to the previous version altered.**

GB