

Printing date: 20.12.2022 Version number 4 (replaces version 3) Revision: 20.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: TOUCH-ON+ Occlusions-Spray

· Article number: 77653500

• 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

- · Application of the substance / the mixture Auxiliary for dental technology
- 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Heimerle + Meule GmbH Dennigstrasse 16 D-75179 Pforzheim

Telefon +49 (0) 7231 940-0 Telefax +49 (0) 7231 940-2199 www.heimerle-meule.com

· Further information obtainable from:

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt Department BASU - Construction / Occupational Safety / Environment sds@heimerle-meule.com

IATA - 24h Emergency Contact - IATA - 24h Emergency Contact - (Dangerous goods emergency number) +49 172 739 6970

· 1.4 Emergency telephone number:

DEUTSCHLAND - GERMANY:

Vergiftungs-Informations-Zentrale Freiburg, ++49 761 19240 (24 h)

(Poisoning Information Center)

GREAT BRITAIN:

National Poisons Information Service +44 121 507 4123

Members of the public seeking specific information on poisons should contact: In England and Wales: NHS 111 - dial 111 - In Scotland: NHS 24 - dial 111

IRELAND

+353 1 809 2166 (7 Days 8 am -10 pm)

Healthcare Professionals: +353 1 809 2566

ITALY:

Istituto Superiore di Sanità (ISS) +3906499906140

Centro Antiveleni

Bergamo: +39 800 883300

Firenze +39 055 794 7819

Milano: +39 055 794 7819

Roma +39 06 68593726

Roma +39 06 49978000

Roma +39 06 3954343

KROATIA - REPUBLIKA HRVATSKA:

(+385) 01 2348 342

ESTLAND - ESTONIA:

Tervisemeti Mürgistusteabekeskuse

National (24/7): 16662

(+372) 7943 794

LETTLAND - LATVIA:

Valsts Toksikoloģijas centrs, Saindēšanās un zāļu informācijas centrs, (24h) 112

(Contd. on page 2)



Printing date: 20.12.2022 Version number 4 (replaces version 3) Revision: 20.12.2022

Trade name: TOUCH-ON+ Occlusions-Spray

(Contd. of page 1)

(24h) +371 67042473

LITAUEN - LIETUVOS RESPUBLIKA:

Poison Information Bureau (24/7), Tel.: +8 5 236 20 52

Apsinuodijimų informacijos biuras

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB



Printing date: 20.12.2022 Version number 4 (replaces version 3) Revision: 20.12.2022

Trade name: TOUCH-ON+ Occlusions-Spray

	(Cont	d. of page 2)
· Dangerous components / Information on ingredients:		
CAS: 74-98-6	propane; propane liquefied	25-50%
EINECS: 200-827-9	♦ Flam. Gas 1A, H220	
Index number: 601-003-00-5	Press. Gas (Comp.), H280	
RTECS: TX 2275000		
CAS: 106-97-8	butane, pure; butane; butane (containing ≥ 0.1 % butadiene (203-	25-50%
EINECS: 203-448-7	450-8))	
Index number: 601-004-00-0	♦ Flam. Gas 1A, H220	
RTECS: EJ 4200000	Acute Tox. 3, H331	
	Press. Gas (Comp.), H280	
Additional information: For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

Involve doctor immediately after a accident or unwell

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Seek immediate medical advice.

Rinse opened eye for several minutes under running water.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Forms explosive mixtures with air on intense heating

- · 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.



Wear self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

GB ·



Printing date: 20.12.2022 Version number 4 (replaces version 3) Revision: 20.12.2022

Trade name: TOUCH-ON+ Occlusions-Spray

(Contd. of page 3)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Suppress gases/fumes/haze with water spray.

Do not allow to enter sewers/surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Dispose of the material collected according to regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Keep receptacles tightly sealed.

he usual precautionary measures are to be adhered to when handling chemicals.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not dry clean dust covered objects and floors. Wash thoroughly with plenty of water.

- · Information about fire and explosion protection: Keep ignition sources away Do not smoke.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage.
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings.

Observe official regulations on storing packagings.

Prevent any seepage into the ground.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Keep container tightly sealed.

Store under lock and key and out of the reach of children.

- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

	· Ingredients with limit values that require monitoring at the workplace: CAS: 74-98-6 propane		
CAS: 74-98-6 propa			
AGW (Germany)	Long-term value: 1800 mg/m³, 1000 ppm 4(II);DFG		
CAS: 106-97-8 buta	CAS: 106-97-8 butane, pure		
WEL (Great Britain,	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)		

(Contd. on page 5)



Printing date: 20.12.2022 Version number 4 (replaces version 3) Revision: 20.12.2022

Trade name: TOUCH-ON+ Occlusions-Spray

(Contd. of page 4)

AGW (Germany) Long-term value: 2400 mg/m^3 , 1000 ppm 4(II);DFG

Regulatory information

AGW (Germany): TRGS 900 WEL (Great Britain): EH40/2020

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device when high concentrations are present.

· Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Natural rubber, NR

Butyl rubber, BR

Nitrile rubber, NBR

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Colourless
Odour:
Characteristic
Odour threshold:
Melting point/freezing point:
Undetermined.

· Boiling point or initial boiling point and boiling

range -44°C (-47.2°F)
• Flammability Not applicable.

(Contd. on page 6)



Printing date: 20.12.2022 Version number 4 (replaces version 3) Revision: 20.12.2022

Trade name: TOUCH-ON+ Occlusions-Spray

(Contd. of page 5)

· Lower and	upper e.	xplosion	limit
-------------	----------	----------	-------

1.5 Vol % · Lower: · Upper: 10.9 Vol %

· Flash point: Not applicable, as aerosol. 365°C (689°F) (Butan) · Ignition temperature: · Decomposition temperature: Not determined.

 $\cdot pH$ Not determined.

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic: Not determined.

·Solubility

Not miscible or difficult to mix. · water:

Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20°C (68°F): 5,000 hPa (3.800 mm Hg)

· Density and/or relative density

Density at 20°C (68°F): $0.56 \text{ g/cm}^3 (4.67 \text{ lbs/gal})$

· Relative density Not determined. Not determined. · Vapour density

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and

environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

Not determined. · Explosive properties:

· Solvent content:

98 % · Organic solvents:

· Change in condition

Not applicable. · Evaporation rate

Information with regard to physical hazard classes

Void · Explosives Void · Flammable gases

· Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable

gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void Void · Corrosive to metals Void · Desensitised explosives

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 7)



Printing date: 20.12.2022 Version number 4 (replaces version 3) Revision: 20.12.2022

Trade name: TOUCH-ON+ Occlusions-Spray

(Contd. of page 6)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Forms explosive gas mixture with air.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity
- · LD/LC50 values relevant for classification:

CAS: 106-97-8 butane, pure

Inhalative LC50/4 h 658 mg/l (rat)

- · 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information


- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment Not applicable.
- · **PBT**: Not applicable.
- · **vPvB**: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

· Waste disposal key:

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

(Contd. on page 8)

Heimerle + Meule

Printing date: 20.12.2022 Version number 4 (replaces version 3) Revision: 20.12.2022

Trade name: TOUCH-ON+ Occlusions-Spray

(Contd. of page 7)

Packaging which is uncleaned or soiled with product remains is to be treated like the product itself Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	UN1950 AEROSOLS AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR 2	
Class Label	2 5F Gases. 2.1
· IMDG, IATA	
Class	2.1 Gases.
Label	2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Code	Warning: Gases. F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity about 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

(Contd. on page 9)

Heimerle + Meule

Printing date: 20.12.2022 Version number 4 (replaces version 3) Revision: 20.12.2022

Trade name: TOUCH-ON+ Occlusions-Spray

	(Contd. of page	
Segregation Code	SG69 For AEROSOLS with a maximum capacity of litre:	
	Segregation as for class 9. Stow "separated from" class except for division 1.4.	
	For AEROSOLS with a capacity above 1 litre:	
	Segregation as for the appropriate subdivision of class 2 For WASTE AEROSOLS:	
	Segregation as for the appropriate subdivision of class 2	
14.7 Maritime transport in bulk accord	ding to IMO	
instruments	Not applicable.	
Transport/Additional information:		
ADR		
Limited quantities (LQ)	IL	
Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
Transport category	2	
<i>IMDG</i>		
Limited quantities (LQ)	IL	
Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
IATA		
Remarks:		
	24h emergency contact -	
	(Dangerous goods emergency number)	
	+49 172 739 6970	
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

GADSL - Global Automotive Declarable Substance List

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 10)



Printing date: 20.12.2022 Version number 4 (replaces version 3) Revision: 20.12.2022

Trade name: TOUCH-ON+ Occlusions-Spray

(Contd. of page 9)

- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

- · Waterhazard class: .
- · Other regulations, limitations and prohibitive regulations -
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Reasons for revise

If necessary, this saftey data sheet can revised according to legal guidelines.

Our current version for your reference is available on our website www.heimerle-meule.com

· Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H331 Toxic if inhaled.

Department issuing SDS:

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt

 $Department\ BASU\ -\ Construction\ /\ Occupational\ Safety\ /\ Environment$

sds@heimerle-meule.com

· Contact:

Herr Thomas Knuth

thomas.knuth@heimerle-meule.com

sds@heimerle-meule.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

AwSV: Ordinance on facilities for handling water-polluting substances (German regulation).

TRGS: Technical rules for hazardous substances (German regulation)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1

: Aerosols – Category 3

Press. Gas (Comp.): Gases under pressure - Compressed gas

Acute Tox. 3: Acute toxicity – Category 3

* Data compared to the previous version altered.