

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.06.2022

Version number 9

Revision: 21.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** Thinner for silver conducting lacquer
Verdünner für Silberleitlack

· **Article number:** 86943300

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
Not approved for private consumers.

· **Application of the substance / the mixture**
Cleaning material/ Detergent
Thinner, Diluent

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Heimerle + Meule GmbH
Dennigstrasse 16
D-75179 Pforzheim

Telefon +49 (0) 7231 940-0
Telefax +49 (0) 7231 940-2199
www.heimerle-meule.com

· **Further information obtainable from:**

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt
Department BASU - Construction / Occupational Safety / Environment
sds@heimerle-meule.com

IATA - 24h Emergency Contact - IATA - 24h Emergency Contact -
(Dangerous goods emergency number)
+49 172 739 6970

· **1.4 Emergency telephone number:**

DEUTSCHLAND - GERMANY:
Vergiftungs-Informations-Zentrale Freiburg, ++49 761 19240 (24 h)
(Poisoning Information Center)

GREAT BRITAIN:
National Poisons Information Service +44 121 507 4123
Members of the public seeking specific information on poisons should contact:
In England and Wales: NHS 111 - dial 111 - In Scotland: NHS 24 - dial 111

ITALY:
Istituto Superiore di Sanità +3906499906140

KROATIA - REPUBLIKA HRVATSKA:
(+385) 01 2348 342

ESTLAND - ESTONIA:
Tervisemeti Mürgistusteabekeskuse 16662, (+342) 7914 794

LETTLAND - LATVIA:
Latvijas Vides, ģeoloģijas un meteoroloģijas centrs (+371) 670 32600

LITAUEN - LIETUVOS RESPUBLIKA:
Apsinuodijimų informacijos biuras +370 (85) 2362052

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.06.2022

Version number 9

Revision: 21.06.2022

Trade name: Thinner for silver conducting lacquer
Verdüner für Silberleitlack

(Contd. of page 1)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008




Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



- Signal word *Danger*
- Hazard-determining components of labelling:
cyclohexanol
1-ethoxypropan-2-ol
Eucalyptus globulus oil
- Hazard statements
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 21.06.2022

Version number 9

Revision: 21.06.2022

Trade name: Thinner for silver conducting lacquer
Verdüner für Silberleitlack

(Contd. of page 2)

P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components / Information on ingredients:**

CAS: 52125-53-8 EINECS: 216-374-5 Index number: 603-177-00-8	1-ethoxypropan-2-ol; 2PG1EE; 1-ethoxy-2-propanol; propylene glycol monoethyl ether Flam. Liq. 3, H226 STOT SE 3, H336	50-<100%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 RTECS: KQ 6300000 Reg.nr.: 01-2119457610-43	ethanol; ethyl alcohol; Alcohol; Ethyl hydroxide; Methyl carbinol Flam. Liq. 2, H225 Eye Irrit. 2, H319	10-<20%
CAS: 108-93-0 EINECS: 203-630-6 Index number: 603-009-00-3 RTECS: GV 7875000	cyclohexanol; Hexahydrophenol; Hexalin Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335	5-<10%
CAS: 84625-32-1	Eucalyptus globulus oil; Dinkum oil; Eucalyptus absolute; Eucalyptus bioabsolute; Eucalyptus globulus extract; Eucalyptus globulus Labile Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1, H317	5-<10%
CAS: 8000-48-4 EINECS: 296-357-7	Eucalyptus spp.; Eucalyptus extract; Eucalyptus globulus extract Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315; Eye Irrit. 2, H319	0.25-<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
 Do not leave affected persons unattended.
 Immediately remove any clothing soiled by the product.
 Personal protection for the First Aider.
 Take affected persons out of danger area and lay down.
 Involve doctor immediately after an accident or unwell
- **After inhalation:**
 Supply fresh air and to be sure call for a doctor.
 In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.06.2022

Version number 9

Revision: 21.06.2022

Trade name: Thinner for silver conducting lacquer
Verdünnern für Silberleitlack

(Contd. of page 3)

- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
Drink plenty of water and provide fresh air. Call for a doctor immediately.
A person vomiting while laying on their back should be turned onto their side.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Can form explosive gas-air mixtures.
- **5.3 Advice for firefighters**
- **Protective equipment:**



Wear self-contained respiratory protective device.

- **Additional information**
Collect contaminated fire fighting water separately. It must not enter the sewage system.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Use respiratory protective device against the effects of fumes/dust/aerosol.
Only handle and refill product in closed systems.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
Ignition source distance
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.06.2022

Version number 9

Revision: 21.06.2022

Trade name: Thinner for silver conducting lacquer
Verdüner für Silberleitlack

(Contd. of page 4)

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Keep away from heat and direct sunlight.

Use only in well ventilated areas.

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

the usual precautionary measures are to be adhered to when handling chemicals.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not dry clean dust covered objects and floors. Wash thoroughly with plenty of water.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings .

Observe official regulations on storing packagings .

Prevent any seepage into the ground.

· **Information about storage in one common storage facility:**

Store away from flammable substances.

Do not store together with materials which also support fire

Store away from foodstuffs.

· **Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Store under lock and key and out of the reach of children.

· **Storage class: 3**

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 64-17-5 ethanol

WEL (Great Britain)	Long-term value: 1920 mg/m ³ , 1000 ppm
AGW (Germany)	Long-term value: 380 mg/m ³ , 200 ppm 4(II);DFG, Y

CAS: 108-93-0 cyclohexanol

WEL (Great Britain)	Long-term value: 208 mg/m ³ , 50 ppm
MAK (Germany)	vgl. Abschn.IIb

· **Regulatory information**

WEL (Great Britain): EH40/2020

AGW (Germany): TRGS 900

MAK (Germany): MAK- und BAT-Liste

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.06.2022

Version number 9

Revision: 21.06.2022

Trade name: Thinner for silver conducting lacquer
Verdüner für Silberleitlack

(Contd. of page 5)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.

Apply solvent resistant skin cream before starting work.

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

According to EC Directive 89/686/EEC

· **Respiratory protection:**

Not necessary if room is well-ventilated.

Use suitable respiratory protective device only when aerosol or mist is formed.

Short term filter device:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire.

according EN 14387

according to EN 143

· **Recommended filter device for short term use:** Combination filter A-P2

· **Protection of hands:**

Solvent resistant gloves

Check protective gloves prior to each use for their proper condition.



Protective gloves

according to EN 374

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

Sensibilisation by the components in the glove materials is possible.

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Prior to working with gloves the rubbing in with tanniferous skin-protecting agents for the avoidance of skin softening due to perspiration is recommended.

· **Material of gloves**

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

· **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 120 - 240 minutes (Permeation according to EN 16523-1:2015: Level 3).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.06.2022

Version number 9

Revision: 21.06.2022

Trade name: Thinner for silver conducting lacquer
Verdüner für Silberleitlack

(Contd. of page 6)

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 3).

Value for the permeation: Level ≤ 3

· **Not suitable are gloves made of the following materials:**

Nitrile rubber, NBR

Natural rubber, NR

Leather gloves

Strong material gloves

· **Eye protection:**



Tightly sealed goggles

according to EN 166

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

Colour: Colourless

· **Odour:** Solvent-like

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 78°C (172.4°F)

· **Flash point:** < 23°C (< 73.4°F)

· **Flammability (solid, gas):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: 1.3 Vol %

Upper: 15 Vol %

· **Vapour pressure at 20°C (68°F):** 59 hPa (44.3 mm Hg)

· **Density at 20°C (68°F):** 0.9 g/cm³ (7.51 lbs/gal)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.06.2022

Version number 9

Revision: 21.06.2022

Trade name: Thinner for silver conducting lacquer
Verdünner für Silberleitlack

(Contd. of page 7)

- | | |
|--|--|
| · Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Reacts with strong oxidising agents.
Reacts with acids, alkalis and oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Inhalative	LC50/4 h	15–30 mg/l
------------	----------	------------

CAS: 64-17-5 ethanol

Oral	LD50	7,060 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/l (rat)

CAS: 108-93-0 cyclohexanol

Oral	LD50	2,060 mg/kg (rat)
Inhalative	LC50/4 h	1.5 mg/l (ATE)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.06.2022

Version number 9

Revision: 21.06.2022

Trade name: Thinner for silver conducting lacquer
Verdüner für Silberleitlack

(Contd. of page 8)


· **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
-
- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment** Not applicable.
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Contact manufacturer for recycling information.
- **Waste disposal key:**
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.
- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Packaging which is uncleaned or soiled with product remains is to be treated like the product itself
Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish
- **Recommended cleansing agents:** Alcohol

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1993

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.06.2022

Version number 9

Revision: 21.06.2022

Trade name: Thinner for silver conducting lacquer
Verdüner für Silberleitlack

(Contd. of page 9)

· **14.2 UN proper shipping name**
· **ADR** *UN1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL), 1-ethoxypropan-2-ol), special provision 640D*

· **IMDG** *FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL), 1-ethoxypropan-2-ol)*

· **IATA** *FLAMMABLE LIQUID, N.O.S. (ETHANOL, 1-ethoxypropan-2-ol)*

· **14.3 Transport hazard class(es)**
· **ADR, IMDG, IATA**



· **Class** *3 Flammable liquids.*
· **Label** *3*

· **14.4 Packing group**
· **ADR, IMDG, IATA** *II*

· **14.5 Environmental hazards:**
· **Marine pollutant:** *No*

· **14.6 Special precautions for user** *Warning: Flammable liquids.*
· **Hazard identification number (Kemler code):** *33*
· **EMS Number:** *F-E,S-E*
· **Stowage Category** *B*

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** *Not applicable.*

· **Transport/Additional information:**

· **ADR**
· **Limited quantities (LQ)** *1L*
· **Excepted quantities (EQ)** *Code: E2*
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· **Transport category** *2*

· **IMDG**
· **Limited quantities (LQ)** *1L*
· **Excepted quantities (EQ)** *Code: E2*
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· **IATA**
· **Remarks:** *24h emergency contact -*
(Dangerous goods emergency number)

+49 172 739 6970

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.06.2022

Version number 9

Revision: 21.06.2022

Trade name: Thinner for silver conducting lacquer
Verdüner für Silberleitlack

(Contd. of page 10)

· **UN "Model Regulation":** UN 1993 FLAMMABLE LIQUID, N.O.S., SPECIAL PROVISION 640D (ETHANOL (ETHYL ALCOHOL), 1-ETHOXYPROPAN-2-OL), 3, II

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

· **GADSL - Global Automotive Declarable Substance List**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P5c FLAMMABLE LIQUIDS**

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	85.0

· **Waterhazard class:** .

· **Other regulations, limitations and prohibitive regulations -**

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Reasons for revise**

If necessary, this safety data sheet can revised according to legal guidelines.

Our current version for your reference is available on our website
www.heimerle-meule.com

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 21.06.2022

Version number 9

Revision: 21.06.2022

Trade name: Thinner for silver conducting lacquer
Verdüner für Silberleitlack

(Contd. of page 11)

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:**

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt
Department BASU - Construction / Occupational Safety / Environment

sds@heimerle-meule.com

· **Contact:**

Herr Thomas Knuth
thomas.knuth@heimerle-meule.com
sds@heimerle-meule.com

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
AwSV: Ordinance on facilities for handling water-polluting substances (German regulation).
TRGS: Technical rules for hazardous substances (German regulation)
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**