

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 23.03.2021

Version number 1

Revision: _____ 23.03.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name: Conducting silver-lacquer**
Silberleitlack

· **Article number:** 77953018

· **UFI:** 22N8-A0PX-V00V-02M7

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
Not approved for private consumers.

· **Application of the substance / the mixture** Lacquer

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Heimerle + Meule GmbH
Dennigstrasse 16
D-75179 Pforzheim

Telefon +49 (0) 7231 940-0
Telefax +49 (0) 7231 940-2199
www.heimerle-meule.com

· **Further information obtainable from:**

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt
Department BASU - Construction / Occupational Safety / Environment
sds@heimerle-meule.com

IATA - 24h Emergency Contact - IATA - 24h Emergency Contact -
(Dangerous goods emergency number)
+49 172 739 6970

· **1.4 Emergency telephone number:**

DEUTSCHLAND - GERMANY:

Vergiftungs-Informationen-Zentrale Freiburg, ++49 761 19240 (24 h)
(Poisoning Information Center)

GREAT BRITAIN:

National Poisons Information Service +44 121 507 4123

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111 - In Scotland: NHS 24 - dial 111

ITALY:

Istituto Superiore di Sanità +3906499906140

KROATIA - REPUBLIKA HRVATSKA:

(+385) 01 2348 342

ESTLAND - ESTONIA:

Tervisemeti Mürgistusteabekeskuse 16662, (+342) 7914 794

LETTLAND - LATVIA:

Latvijas Vides, ģeoloģijas un meteoroloģijas centrs (+371) 670 32600

LITAUEN - LIETUVOS RESPUBLIKA:

Apsinuodijimų informacijos biuras +370 (85) 2362052

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 23.03.2021

Version number 1

Revision: _____ 23.03.2021

Trade name: Conducting silver-lacquer
Silberleitlack

(Contd. of page 1)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS02



GHS05



GHS07



GHS09

- Signal word *Danger*
- Hazard-determining components of labelling:
 - butanol
 - n-butyl acetate
- Hazard statements
 - H226 Flammable liquid and vapour.
 - H318 Causes serious eye damage.
 - H336 May cause drowsiness or dizziness.
 - H410 Very toxic to aquatic life with long lasting effects.
- Precautionary statements
 - P273 Avoid release to the environment.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 23.03.2021

Version number 1

Revision: _____ 23.03.2021

Trade name: Conducting silver-lacquer
Silberleitlack

(Contd. of page 2)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

EUH208 Contains methyl methacrylate. May produce an allergic reaction.

· **Labelling of packages where the contents do not exceed 125 ml**

· **Hazard pictograms**



· **Signal word** Danger

· **Hazard-determining components of labelling:**

butanol

n-butyl acetate

· **Hazard statements**

H318 Causes serious eye damage.

· **Precautionary statements**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components / Information on ingredients:**

CAS: 7440-22-4 EINECS: 231-131-3	silver; silver < 1mm particle size; Silver (Powder <0.0001mm); Nano silver as per EU recommended definition; Silver (Powder <1mm)	≥25–≤50%
	⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 23.03.2021

Version number 1

Revision: _____ 23.03.2021

Trade name: Conducting silver-lacquer
Silberleitlack

(Contd. of page 3)

CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 RTECS: AF 7350000	<i>n</i> -butyl acetate; Butyl acetate; 1-Acetoxybutane; Acetic acid, butyl ester; Butyl ethanoate; TBAC ----- ☠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	10–25%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 RTECS: EO 1400000	butanol; butyl alcohol (except tert-butyl alcohol); butan-1-ol; <i>n</i> -butanol; Butyl alcohol; 1-Butanol; Butyl hydroxide; Eastman <i>n</i> -Butyl Alcohol; <i>n</i> -Butyl alcohol ----- ☠ Flam. Liq. 3, H226 ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥3–≤7%
CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6 RTECS: OZ 5075000	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate ----- ☠ Flam. Liq. 2, H225 ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥0.5–<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:**

Immediately remove any clothing soiled by the product.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

Involve doctor immediately after a accident or unwell

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Drink plenty of water and provide fresh air. Call for a doctor immediately.

A person vomiting while laying on their back should be turned onto their side.

Rinse out mouth and then drink plenty of water.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 23.03.2021

Version number 1

Revision: _____ 23.03.2021

Trade name: Conducting silver-lacquer
Silberleitlack

(Contd. of page 4)

- **5.3 Advice for firefighters**
- **Protective equipment:**



Wear self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire

- **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Only handle and refill product in closed systems.

- **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

the usual precautionary measures are to be adhered to when handling chemicals.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not dry clean dust covered objects and floors. Wash thoroughly with plenty of water.

- **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings .

Observe official regulations on storing packagings .

Prevent any seepage into the ground.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 23.03.2021

Version number 1

Revision: _____ 23.03.2021

Trade name: Conducting silver-lacquer
Silberleitlack

(Contd. of page 5)

- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store under lock and key and out of the reach of children.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 123-86-4 n-butyl acetate

WEL (Great Britain)	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
IOELV (European Union)	Short-term value: 723 mg/m ³ , 150 ppm Long-term value: 241 mg/m ³ , 50 ppm
AGW (Germany)	Long-term value: 300 mg/m ³ , 62 ppm 2(I);AGS, Y

CAS: 56-81-5 glycerol

WEL (Great Britain)	Long-term value: 10 mg/m ³
AGW (Germany)	Long-term value: 200 E mg/m ³ 2 (I);DFG, Y

CAS: 71-36-3 butanol

WEL (Great Britain)	Short-term value: 154 mg/m ³ , 50 ppm Sk
AGW (Germany)	Long-term value: 310 mg/m ³ , 100 ppm 1(I);DFG, Y

CAS: 80-62-6 methyl methacrylate

WEL (Great Britain)	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm
IOELV (European Union)	Short-term value: 100 ppm Long-term value: 50 ppm
AGW (Germany)	Long-term value: 210 mg/m ³ , 50 ppm 2(I);DFG, EU, Y

· **Regulatory information**

WEL (Great Britain): EH40/2020
IOELV (European Union): (EU) 2019/1831
AGW (Germany): TRGS 900

· **Ingredients with biological limit values:**

CAS: 71-36-3 butanol

BGW (Germany)	2 mg/g Kreatinin Untersuchungsmaterial: Urin Probennahmezeitpunkt: vor nachfolgender Schicht Parameter: Butan-1-ol (1-Butanol) (nach Hydrolyse)
	10 mg/g Kreatinin Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Butan-1-ol (1-Butanol) (nach Hydrolyse)

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 23.03.2021

Version number 1

Revision: _____ 23.03.2021

Trade name: Conducting silver-lacquer
Silberleitlack

(Contd. of page 6)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

According to EC Directive 89/686/EEC

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire.

according EN 14387

according to EN 143

· **Protection of hands:**



Protective gloves

according to EN 374

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

Sensibilisation by the components in the glove materials is possible.

Check the permeability prior to each anewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Prior to working with gloves the rubbing in with tanniferous skin-protecting agents for the avoidance of skin softening due to perspiration is recommended.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 3).

Value for the permeation: Level ≤ 3

· **Not suitable are gloves made of the following materials:**

Leather gloves

Strong material gloves

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 23.03.2021

Version number 1

Revision: _____ 23.03.2021

Trade name: Conducting silver-lacquer
Silberleitlack

(Contd. of page 7)

· **Eye protection:**

Tightly sealed goggles

according to EN 166

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

· Form:	Fluid
· Colour:	Silver grey
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.· **Change in condition**

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	Undetermined.

· **Flash point:** 23 - 60°C (73.4 - 140°F)· **Flammability (solid, gas):** Not applicable.· **Ignition temperature:** >300°C (>572°F)· **Decomposition temperature:** Not determined.· **Auto-ignition temperature:** Product is not selfigniting.· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.· **Explosion limits:**

· Lower:	Not determined.
· Upper:	Not determined.

· **Vapour pressure:** Not determined.· **Density at 20°C (68°F):** 1.4 g/cm³ (11.68 lbs/gal)· **Relative density** Not determined.· **Vapour density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:** Not determined.· **Viscosity:**

· Dynamic:	Not determined.
· Kinematic:	Not determined.

· **Solvent content:**· **Organic solvents:** 50–<54 %

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 23.03.2021

Version number 1

Revision: _____ 23.03.2021

Trade name: Conducting silver-lacquer
Silberleitlack

(Contd. of page 8)

Solids content:	40–45 %
------------------------	---------

· 9.2 Other information	26–<30 %
--------------------------------	----------

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with acids, alkalis and oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	15,800–79,000 mg/kg (rat)
------	------	---------------------------

CAS: 123-86-4 n-butyl acetate

Oral	LD50	14,000 mg/kg (rat)
------	------	--------------------

Inhalative	LC50/4 h	>21 mg/l (rat)
------------	----------	----------------

CAS: 56-81-5 glycerol

Oral	LD50	12,600 mg/kg (Rat)
------	------	--------------------

Dermal	LD50	10,000 mg/kg (Kanninchen)
--------	------	---------------------------

CAS: 71-36-3 butanol

Oral	LD50	790 mg/kg (rat)
------	------	-----------------

Dermal	LD50	3,400 mg/kg (rbt)
--------	------	-------------------

Inhalative	LC50/4 h	8,000 mg/l (rat)
------------	----------	------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 23.03.2021

Version number 1

Revision: _____ 23.03.2021

Trade name: Conducting silver-lacquer
Silberleitlack

(Contd. of page 9)

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 7440-22-4 silver

(Chronische) aquatische Toxizität	0.00012 mg/l (Fisch)
	0.0008 mg/l (wirbellose Wasserlebewesen)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.

· **12.5 Results of PBT and vPvB assessment** Not applicable.

· **PBT:** Not applicable.


· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

· **Waste disposal key:**

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP14	Ecotoxic

· **Uncleaned packaging:**

· **Recommendation:**

Disposal must be made according to official regulations.

Packaging which is uncleaned or soiled with product remains is to be treated like the product itself

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 23.03.2021

Version number 1



Revision: _____ 23.03.2021

Trade name: Conducting silver-lacquer
Silberleitlack

(Contd. of page 10)

Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UNI263
· 14.2 UN proper shipping name · ADR · IMDG, IATA	UNI263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT
· 14.3 Transport hazard class(es) · ADR	
· Class · Label	3 Flammable liquids. 3
· IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E, S-E A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	3 D/E

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 23.03.2021

Version number 1

Revision: _____ 23.03.2021

Trade name: Conducting silver-lacquer
Silberleitlack

(Contd. of page 11)

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml

· IATA	
· Remarks:	24h emergency contact - (Dangerous goods emergency number)
	+49 172 739 6970
· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **GADSL - Global Automotive Declarable Substance List**

CAS: 7440-22-4	silver	D(LR)
----------------	--------	-------

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	50–100

· **Waterhazard class:** .

· **Other regulations, limitations and prohibitive regulations -**

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 23.03.2021

Version number 1

Revision: _____ 23.03.2021

Trade name: Conducting silver-lacquer
Silberleitlack

(Contd. of page 12)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Reasons for revise**

If necessary, this safety data sheet can be revised according to legal guidelines.

Our current version for your reference is available on our website
www.heimerle-meule.com

· **Relevant phrases**

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

· **Department issuing SDS:**

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt
Department BASU - Construction / Occupational Safety / Environment

sds@heimerle-meule.com

· **Contact:**

Herr Thomas Knuth
Knuth@heimerle-meule.com
sds@heimerle-meule.com

· **Abbreviations and acronyms:**

AwSV: Ordinance on facilities for handling water-polluting substances (German regulation).
TRGS: Technical rules for hazardous substances (German regulation)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity - oral – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1