

ECOFLAMM

Compact and powerful flame-casting unit


The economical solution for melting precious as well as non-precious alloys.

The proven centrifugal casting principle with adjustable extraction speed and adjustable centrifuge time ensures reliable casting of the finest structures, as well as a homogeneous alloy microstructure.



Technical data	
Height	330 mm
Width	600 mm
Depth	550 mm
Voltage	230/V 50 – 60 Hz
Power consumption	2000 W
Weight	41 kg

ECOFLAMM basic unit	7763 3 001	2,128.00 €
Including		
Sprue former and 4 investment rings		
Flame protection plate for burner		
2 universal smelting moulds		
Alloy chute, goggles, lighter		
Allen key, instructions for use		



Burner Set (Fig.1)	7763 3 022	565.00 €
consisting of		
Easy handle with mounted autogenous welding hoses for propane gas and oxygen, 3 m long	7763 3 009	108.00 €
Crown burner for melting	7763 3 010	98.00 €
Solder torch	7763 3 011	114.00 €
Pressure reducing valve for oxygen	7763 3 005	76.00 €
Pressure reducing valve for propane gas	7763 3 006	76.00 €
Flame arrester oxygen	7763 3 007	40.00 €
Flame arrester propane gas	7763 3 008	40.00 €
Open-end wrench SW 30 x 32	7763 3 019	13.00 €

Accessories		
Gas saving set (Fig. 2)	7763 3 023	259.00 €
consisting of		
Gas saving apparatus	7763 3 004	190.00 €
Mounting bracket	7763 3 018	12.00 €
Autogenous welding hoses for propane gas and oxygen, 5 m long	7763 3 014	57.00 €
Micro solder insert with 3 interchangeable needle nozzles (Fig. 3)	7763 3 012	110.00 €
Extension hoses for propane gas and oxygen incl. double threaded fitting, 5 m long (Fig. 4)	7763 3 020	62.00 €
5 universal smelting moulds	7763 3 002	55.50 €