

Printing date: 18.04.2016 Version number 1 Revision:\_\_\_\_\_\_\_18.04.2016

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: TOUCH-ON+ Occlusions-Spray

· Article number: 77653500

· 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

- · Application of the substance / the mixture Auxiliary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Heimerle + Meule GmbH Dennigstrasse 16 D-75179 Pforzheim

Telefon +49 (0) 7231 940-0 Telefax +49 (0) 7231 940-2199

www.heimerle-meule.com

\_

· Further information obtainable from:

Department chemistry and environment Abteilung Chemie und Umwelt

· 1.4 Emergency telephone number:

Phone: +49 172 739 6970

sds@heimerle-meule.com

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

(Contd. on page 2)



Trade name: TOUCH-ON+ Occlusions-Spray

(Contd. of page 1)

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

- · Labelling of packages where the contents do not exceed 125 ml
- · Hazard pictograms



- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

*P211* Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

#### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components / Info	Dangerous components / Information on ingredients:		
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 RTECS: TX 2275000	propane	♦ Flam. Gas 1, H220         Press. Gas C, H280	25-50%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 RTECS: EJ 4200000	butane	<b>6</b> Flam. Gas 1, H220 Press. Gas C, H280	25-50%

<sup>·</sup> Additional information: For the wording of the listed risk phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information:

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

Involve doctor immediately after a accident or unwell

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Seek immediate medical advice.

Rinse opened eye for several minutes under running water.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Trade name: TOUCH-ON+ Occlusions-Spray

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### <u>SECTION 5: Firefighting measures</u>

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Forms explosive mixtures with air on intense heating

- · 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Suppress gases/fumes/haze with water spray.
- $\cdot$  6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Dispose of the material collected according to regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

he usual precautionary measures are to be adhered to when handling chemicals.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Store under lock and key and out of the reach of children.

(Contd. on page 4)



Trade name: TOUCH-ON+ Occlusions-Spray

(Contd. of page 3)

Protect from heat and direct sunlight.

- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

74-98-6 propane	74-98-6 propane		
AGW (Germany)	Long-term value: 1800 mg/m³, 1000 ppm 4(II);DFG		
106-97-8 butane			
WEL (Great Britain	) Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1,3-diene)		
AGW (Germany)	Long-term value: 2400 mg/m³, 1000 ppm 4(II);DFG		

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device when high concentrations are present.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 5)



Printing date: 18.04.2016 Version number 1 Revision:\_\_\_\_\_\_\_18.04.2016

Trade name: TOUCH-ON+ Occlusions-Spray

· Body protection: Protective work clothing

(Contd. of page 4)

### SECTION 9: Physical and chemical properties

· 9.1 Information on	basic	physical	and	chemical	properties
----------------------	-------	----------	-----	----------	------------

· General Information

· Appearance:

Form: Aerosol

Colour: According to product specification

Not applicable.

Odour: CharacteristicOdour threshold: Not determined.

· pH-value:
· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: -44 °C (-47 °F)

· Flash point: Not applicable, as aerosol.

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 365 °C (689 °F) (Butan)

• Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

 Lower:
 1,5 Vol %

 Upper:
 10,9 Vol %

• Vapour pressure at 20 °C (68 °F): 5000 hPa (3750 mm Hg)

• Density at 20 °C (68 °F): 0,56 g/cm³ (4.673 lbs/gal) • Relative density Not determined.

Vapour density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:Not determined.Kinematic:Not determined.

· Solvent content:

Organic solvents: 98 %

Solids content: < 5 %

• 9.2 Other information No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)



Trade name: TOUCH-ON+ Occlusions-Spray

(Contd. of page 5)

- · 10.3 Possibility of hazardous reactions Forms explosive gas mixture with air.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

106-97-8 butane

Inhalative LC50/4 h 658 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Generally not hazardous for water
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- $\cdot \textbf{12.6 Other adverse effects} \ \textit{No further relevant information available}.$

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Contact manufacturer for recycling information.
- · Waste disposal key:

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

· European waste catalogue			
	16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST	
Ī	16 05 00	gases in pressure containers and discarded chemicals	
-	16 05 04*	gases in pressure containers (including halons) containing hazardous substances	
-			(C

(Contd. on page 7)



Trade name: TOUCH-ON+ Occlusions-Spray

(Contd. of page 6)

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Packaging which is uncleaned or soiled with product remains is to be treated like the product itself Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish

14.1 UN-Number ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	UN1950 AEROSOLS AEROSOLS Aerosols, flammable
· 14.3 Transport hazard class(es)	
ADR	
· Class · Label	2 5F Gases. 2.1
· Class	2.1
· Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Code	Warning: Gases F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre Category A. For AEROSOLS with a capacity above 1 litre Category B. For WASTE AEROSOLS: Category C, Clea

(Contd. on page 8)



Trade name: TOUCH-ON+ Occlusions-Spray

	(Contd. of page
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriation of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to A	nnex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
$\cdot ADR$	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

#### · TSCA (Toxic Substances Control Act)

All ingredients are listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

- · Waterhazard class: Generally not hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Trade name: TOUCH-ON+ Occlusions-Spray

(Contd. of page 8)

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Reasons for revise

If necessary, this saftey data sheet can revised according to legal guidelines.

Our current version for your reference is available on our website www.heimerle-meule.com

· Date from last issue : Version 1

#### · Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

· Department issuing MSDS: Department chemistry and environment

#### · Contact:

Herr Thomas Knuth

Knuth@heimerle-meule.com

sds@heimerle-meule.com

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases, Hazard Category 1

Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

-GB